



CATALOG NUMBER

2

LIGHTING-INC. ST. LOUIS-MISSOURI

E. R. BEERS ELEC. CO. PA.

DAY-BRITE FIXTURES OMSBURG, PA!

CATALOG No. 112

Fluorescent lamps are revolutionary new light sources. They are tubular in shape and coated on the inside with special Fluorescent powders which glow when stimulated by short-wave ultra-violet light. They have no filament. One lamp gives a daylight color which is almost a perfect match for north sky light. Other colors are: White, Blue, Green, Gold, Pink and Red.

CONSTRUCTION

Fluorescent lamps are available in two diameters and four lengths. There is a $1\frac{1}{2}$ " diameter lamp of low surface brightness for exposed use, and a 1" diameter lamp of high brightness for confined spaces and concealed use. The 18" lamp is available in both the 1" and $1\frac{1}{2}$ " diameter size, the 24" lamp in the $1\frac{1}{2}$ " diameter size, the 36" lamp in the 1" diameter size and the 48" lamp in the $1\frac{1}{2}$ " diameter size.

A sturdy 2-pin base is at each end of all lamps. Sockets are strong and thin, allowing lamps to be mounted end to end, in lines or pairs.

These lamps are designed to operate on standard alternating current low-voltage circuits and require a small ballast and lamp starter to supply low voltage to the lamp itself. These ballasts are mounted in the fixture housing in practically all instances. The lamp starters are mounted in special receptacles adjacent to one of the lamp sockets and are easily removable for replacement.

ADVANTAGES

Style. The size and shape of Fluorescent lamps allow freedom of application for creative lighting. They may be used exposed or concealed in troughs, counters, niches, and backgrounds. In fact there is practically no limit to their application.

Brightness. The low surface brightness of the $1\frac{1}{2}$ lamp allows its use, fully exposed, for direct lighting to high levels of illumination when properly designed fixtures are used in correctly engineered recommendations. The higher brightness of the 1" lamp makes it an effective tool for attraction lighting.

Coolness. Only 50% of the radiated heat of incandescent lamps. No concentration of heat in one spot. Ideal for air conditioned interiors and for display lighting of perishable foods and merchandise.

Color. White is cooler and softer in appearance than regular incandescent lamps. Daylight color is effective in many color-matching and inspection operations. It shows merchandise in its true outdoor appearance. Other colors have various applications for display work and have a glowing quality obtainable only with Fluorescence.

Efficiency. Fluorescent lamps are among the most efficient lamps ever developed. Lumen values are high and are well maintained throughout the useful life of the lamp. While high in output they have nevertheless a low surface brightness and may often be used, fully exposed, in decorative forms without excessive glare.

CONTROL EQUIPMENT

All Day-Brite fixtures are designed to accommodate new type lamp starters and ballasts as manufactured and distributed by leading sources of supply for such material. All fixtures using Tulamp ballasts for 30- and 40-watt lamps include starting compensators.

All fixtures furnished wired with lamp starters and ballasts are tested by us before shipment. However, inasmuch as the lamp starters and ballasts are not manufactured by us we cannot be responsible for defects. This material carries a definite guarantee by its manufacturer. In case of defects we suggest contacting the local agent of the manufacturer.

Note. All latest type control equipment, consisting of lamp starters and ballasts for Fluorescent lamps, is made to operate on Alternating Current only.

Lamps Are Not Included With Any Fixtures


18" 15-watt T-8 **Fluorescent** Lamps are Available in **Various Sizes** As Illustrated



FOR DISPLAY LIGHTING

WALLCASE FIXTURES

For $18^{\prime\prime}$, $24^{\prime\prime}$, $36^{\prime\prime}$ and $48^{\prime\prime}$ Fluorescent Lamps




TYPICAL WALL CASE INSTALLATIONS



Zeller's, Ltd., Edmonton, Alberta, Canada



The F. & R. Lazarus & Co., Columbus, Ohio



The Highee Company, Cleveland, Ohio



Available as Units and in Continuous Lengths

For wallcases, island display cases, wall niches, small display windows, etc. These fixtures are constructed of steel and finished in aluminum lacquer. Other lacquer finishes are available on special order.


Porcelain Enamel reflectors are used in all fixtures assuring maximum diffuse reflection and true color rendition. Merchandise displayed under this type of lighting is brought out to its best advantage.

ANGLE CUT-OFF TYPE LENGTH Catalog Na. Weight Each Lamp Length Lamp Size Far One Lamp Far Each 5½ lbs. 6½ lbs. 10 lbs. 181/4" 412 18"-15w-110v 18" 24¹/₄" 36¹/₄" 413 414A 24"-20w-110v 24" 36"-30w-220v 36" 36"-30w-110v 414B 36" 361/4 11 lbs. 13 lbs. 48"-40w-220v 415A 481 48" 48"-40w-110v 415B 481/ 48" 15 lbs.

Nos. 412, 413, 414A, 414B, 415A, 415B

Catalog		LE	LENGTH			
No.	Lamp Size	For One Lamp	For Each Addl. Lamp	Weight Each Lamp Length		
422	18″-15w-110v	181/4"	18"	6 lbs.		
423	24"-20w-110v	241/4"	24"	7 lbs.		
424A	36"-30w-220v	361/4"	36"	11 lbs.		
424B	36"-30w-110v	361/4"	36"	12 lbs.		
425A	48"-40w-220v	481/4"	48"	14 lbs.		
425B	48"-40w-110v	481/4"	48"	15 lbs.		

STRAIGHT CUT-OFF TYPE



Nos. 422, 423, 424A, 424B, 425A, 425B


When Ordering - Give overall length of fixture to be furnished and number and size of lamps.


Wiring — All fixtures are furnished wired, including lamp starters and ballasts. 24" wire lead is provided at each end.

For Electrical Connection and Switch — Both units and continuous fixtures have 1/2" knockouts at each end for electrical connection. A 3/8" diameter knockout is located in reflector for installation of toggle or levolier switch.


Standard Package — One complete fixture, any style or size.

Efficient . . . and Easy to Install






STRAIGHT CUT-OFF TYPE FOR SHALLOW CASES



For 18" and 36", T-8 Fluorescent Lamps

Schedule S Discounts

For Showcases and Small Wallcases



Unwired Units with Built-In Lamp Starters, But No **Provisions for Mounting Ballasts in Fixtures**

Single unwired units designed for showcases, display cases and small wallcase lighting. For one lamp 18" and 36", T-8 only.

Fixture body has junction box and straight connector at each end. Lamp starters, sockets, hanging clips and screws for installation are included. Indicate type hanging clips required when ordering. See illustration. The connectors at each end will accommodate $\frac{1}{2}$ " tubing or $\frac{5}{16}$ " steel flexible conduit.

Note — Indicate finish when ordering. Chromium finish available; extra.

Cat. Na.	Made af	Na.	OR LAMPS Size	Length*	Standard Finish		Weight Each Lbs.
140	Steel	11	18″-15w	233/4"	Stat. Bronze or Satin Nick. Plt.	4	3
141	Brass	1	18″-15w	233/4"	Stat. Bronze or Satin Nick. Plt.	4	3 3
142	Steel	1	18″–15w	233/4"	Stat. Bronze or Alum. Lacquer	4	3
143	Steel	1	36″-30w	413/4"	Stat. Bronze or Satin Nick. Plt.	4	5
144	Brass	1	36"-30w	413/4"	Stat. Bronze or Satin Nick. Plt.	4	5
145	Steel	1	36″-30w	413/4"	Stat. Bronze or Alum. Lacquer	4	5

*This does not include connectors at ends. Connectors, 1/2" each.



No. 12B No. 13

No. 14B

No. 17


No. 19A


Tubing, fittings and parts to be used with onelight showcase units are illustrated here.

FITTINGS

Illustrating hanging clips furnished with one-light showcase fixtures. Specify type when ordering. Unless specified Type C will be furnished.

HANGING CLIPS







COLOR-MATCHING FIXTURES

Over-Showcase Units For 18" Fluorescent Lamps


Color-matching fixtures for use over showcases where merchandise requires high intensity, daylight quality illumination as an added sales help. Daylight color lamps should be used in these fixtures.

The lamp starters and ballasts are located in the cast base which is of sufficient weight to prevent fixture from tipping.


Furnished completely wired with ballasts, lamp starters, switch and 9-foot cord and plug. Lamps are not included.

Cat.		FOR LAMPS	DIMI	DIMENSIONS		
No.			Overall Height	Pkg.	Each	
914 915	1 2	18″-15w-110v 18″-15w-110v	18" 18"	21" 21"	1 1	20 lbs. 22 lbs.


- Two finishes are available; dark brown baked wrinkle base and body with reeded tubing in two shades of bronze; and light gray wrinkle base and body with reeded tubing in oxidized nickel. Specify brown or gray when ordering.



Typical Showcase Installations



For Small Displays, Wall Niches, etc.



4-One-Light No. 915 — Two-Light



ST. LOUIS, MISSOURI


SHOWCASE LIGHTING

CONTINUOUS SHOWCASE FIXTURES


For 18" and 36" T-8 Fluorescent Lamps



TYPICAL SHOWCASE INSTALLATIONS



The Higbee Company, Cleveland, Ohio



Stix, Baer & Fuller, St. Louis, Missouri



Rhodes Department Store Tacoma, Washington



ST. LOUIS, MISSOURI

No. 1400 With Built-In Lamp Starters

BALLASTS TO BE LOCATED IN BASE OF CASE

Small, efficient showcase fixtures for Fluorescent lamps. These low wattage lamps are especially desirable for use where excessive heat would be detrimental to products displayed and in air-conditioned interiors where heat is an important factor.

For close spacing of lamps to provide for maximum number in a given length of trough, it is necessary to mount the ballast at some convenient location in base of case. Special ballast and switch boxes complete with ballasts and toggle switch control can be furnished for this purpose. They are listed in detail on page 5. These fixtures are furnished wired with sufficient lead to reach ballasts.

Down Tubing - Complete set of fittings and parts for electrical connections from end of fixture to ballast and switch box in base of case can be furnished. See listing on page 5.


Finishes — Any Standard Color Lacquer on steel. Statuary Bronze or Satin Nickel plated finish on steel or brass. Other plated finishes available.

Mounting - Fixtures are mounted with any of the hanging clips shown on page 5, specify type when ordering.

Compact in Design Efficient Porcelain **Enamel Reflector**

Day-Brite showcase fixtures have been engineered to produce the maximum amount of light in the smallest practical cross section size. Lamps are concealed from view of customer and also from clerk standing in back of case. Body of fixture has been designed for beauty and appearance and for rigid construction. Body metal thickness, 18 B&S gauge.

Porcelain Enamel Reflecting Surface has been selected for this showcase fixture because of its high and permanent efficiency and diffuse reflecting qualities. Also because this surface will reflect the true color qualities of Fluorescent lamps. This is particularly desirable in the display of merchandise for true color values.



CATALOG No. 1400								
Minimum Fixture Length Including Lamp Starters	For Numl	ber Lamps	Weight					
and Elbow	18"	36"	Each					
243/4"	1		5 lbs.					
423/4"		1	8 lbs.					
631/2"	1	1	16 lbs.					
811/2"		2	20 lbs.					
1021/4"	1	2	25 lbs.					
1201/4"		3	29 lbs.					

NOTE—Schedule shows minimum length of fixtures for a given number of lamps. However, we recommend that fixtures be purchosed to fit exoct available space inside of showcase.


WHEN ORDERING

- (1) Give exact inside measurements of case—length, width and height.
- (2) Indicate number of lamps and size.
- (3) State finish.
- (4) Specify at which end of fixture elbow for down tubing is to be located. Face
- back of showcase to specify end to have fittings.
- (5) If end fittings and tubing are to be furnished, specify type — see page 5.
- (6) Specify type hangers see page 5. Unless specified, Type C will be furnished.

FITTINGS AND PARTS FOR CONTINUOUS SHOWCASE FIXTURES


DOWN TUBING

For Electrical Connections to Ballasts and Switch Boxes



Style FY Down Tubing— Consists of all tubing and fittings for electrical connections through bottom of case at **front** corner. Ballasts and switch boxes not included.

Style FZ Down Tubing— Consists of all tubing and fittings for electrical connection through bottom of case at **back** corner. Ballasts and switch boxes not included.



BALLAST BOXES FOR CONCEALED MOUNTING


These Ballast Boxes are mounted concealed in base of case and accommodate ballasts as listed in schedule.

Knockouts are provided for electrical connections. **Ballasts are not included. Standard Package**—One



Cat. Na.	Accommodates Number of Ballasts for Lamps	Length of Box	Weight Each Lbs.
1440	1—18"	12"	3
1441		18"	5
1442		32"	8
1443		46"	11

FLUSH TYPE SWITCH BOXES WITH BALLASTS




To be mounted flush in base of case. Complete with ballasts and toggle switch control, but NOT wired. Knockouts are provided in box for electrical connections. For 110 volt A.C. operation.

Catalog	Includes Ballasts		Approx.		
No.	For Lamps	Height	Depth	Length	Weight Each
1444	1—18''—15w	3''	6''	113/4"	8 lbs.
1445	1—36''—30w	3''	6''	1134"*	10 lbs.
1446	1—18"—15w and 1—36"—30w	3''	6''	171/4"	11 lbs.
1447	2—36"—30w	3''	6''	171/4"	15 lbs.
1448	2-36"-30w and 1-18"-15w	3''	6''	171/4"	16 lbs.
1449	3—36''—30w	3''	6''	171/4"	18 lbs.


*Note—If furnished with High P-F ballast, 171/4" box will be provided.

NEW TYPE SOCKETS AND LAMP STARTERS

New Type Sockets with lamp starter block attached are furnished with these fixtures. Lamp starters are easily accessible for replacement and lamps are easily installed or removed with special feature provided in socket.



MITERED AND CURVED SECTIONS




When ordering mitered sections send full size template or accurate detail of miter. Minimum length of sections to accommodate one 18'' lamp and lamp starter is $21^{1}/2''$.


Curved Sections — Curved fixtures for Fluorescent lamps are not available. If curved sections are to be furnished in conjunction with Fluorescent lamp installations, we suggest using same design fixture as illustrated above, except for T-6½ Tubular lamp. These lamps can be secured in Daylight color.

Arranged For Easy Installation


HANGING CLIPS

Illustrating hanging clips furnished with continuous showcase fixtures. Specify type when ordering.





Easily installed and easily maintained. Correctly designed to shield the eyes of both the clerk and the customer from any glare.





COMPLETE WIRED SHOWCASE ASSEMBLIES

TO FIT ANY STANDARD SHOWCASE UP TO 10 FEET

For 18" and 36" T-8 Fluorescent Lamps


These assemblies are furnished complete with tubing, tubing straps, elbows, straight connectors, flexible conduit, box connectors, ballast boxes and hanging clips. Specify type hanger clips required when ordering. See page 7. Unless specified, Type C will be furnished.

The tubing is furnished in sufficient lengths for maximum case length to run across top of case and

in 36" lengths to run down front corner to floor of case. It can be cut on the job to fit exact inside measurements of the showcase.

Ballast boxes are to be located in base of case. Lamp starters are located in the fixture body, and fixtures are wired **but ballasts are not included.**


Standard Package — One complete assembly.



COMPLETE WIRED SHOWCASE ASSEMBLIES

TO FIT ANY STANDARD SHOWCASE UP TO 10 FEET

For 18" and 36" T-8 Fluorescent Lamps




TYPICAL SHOWCASE INSTALLATION ILLUSTRATED ABOVE



EFFICIENT AND COMPACT IN DESIGN . . . EASY TO INSTALL

Day-Brite showcase fixtures have been engineered to produce the maximum amount of light in the smallest practical cross section size. Lamps are concealed from view of customer and also from clerk standing in back of case. Body of fixture has been designed for beauty and appearance and for rigid construction. Body metal thickness, 18 B&S gauge.

Fixtures are designed for easy installation and are furnished complete with all necessary parts and fittings for complete installation.




Type G

Type E

Type F


Illustrating Hanging Clips furnished with Showcase Assemblies. Specify type when ordering.

Fitting-Mirror Lighting




Typical Fitting Room Installation


Easy to Install



For Fitting Tables



For Dressing Tables






FITTING ROOM FIXTURES

For $18^{\prime\prime}$, $24^{\prime\prime}$, $36^{\prime\prime}$ and $48^{\prime\prime}$ Fluorescent Lamps

These fixtures are designed for installation over fitting mirrors and direct the light on the garment being fitted.


Daylight lamps are recommended for use in these fixtures because of their color-correcting qualities and cool effect. Specially designed specular Alzak reflectors are used in these units to assure proper distribution of illumination and to give added punch. Levolier pull switches are included with all fixtures and are located at right end.

All fixtures are wired, ballasts and lamp starters included. Keyhole slots are located in back for easy installation and a $\frac{1}{2}$ knockout for electrical connections is located in back of fixture at center.



Nos. 2950, 2952, 2960A, 2960B, 2962A and 2962B can be furnished finished in Statuary Bronze or Aluminum Lacquer.

Nos. 2951, 2953, 2961A, 2961B, 2963A and 2963B can be furnished plated in Statuary Bronze or Satin Nickel.



Schedule O Discounts

CATAL	CATALOG No.		FOR LAMPS		Standard	Weight	
Lacquer Finish	Plated Finish	No.	Size	Length		Each	
2950 2952 2960A 2960B 2962A 2962B	2951 2953 2961A 2961B 2963A 2963B	1 1 1 1 1			4 4 4 4 4 4	7 lbs. 8 lbs. 10 lbs. 11 lbs. 13 lbs. 14 lbs.	

FITTING AND DRESSING TABLE UNITS


For 18" and 24" Fluorescent Lamps

These units have many applications on fitting tables, dressing tables, and as decorative units in residences, clubs, hotels, etc. They are manufactured in two sizes for one 18" and one 24", $1^{1}/_{2}$ " diameter lamps. The cast ornamental base provides substantial footing.

Fixtures are completely wired with lamp starters, ballasts, 9-foot cord and plug and switch. For 110 volt A.C. operation. Made of aluminum and furnished in a combination baked wrinkle and polished finish.

Schedule S Discounts

	FOR	LAMPS	Overall	Std.	Weight	
CATALOG No.	No.	Size	Height	Pkg.	Each	
965 966	1	18" 24"	191/ ₄ " 251/ ₄ "	2 2	7 lbs. 8 lbs.	



No. 965—For One 18" Lamp No. 966—For One 24" Lamp

BANK CAGE FIXTURES

For $18^{\prime\prime}$, $24^{\prime\prime}$, $36^{\prime\prime}$ and $48^{\prime\prime}$ Fluorescent Lamps

Two styles of fixtures are listed. Open type and with louvers. Open type fixture is designed so that lamp is shielded from the eyes of the teller in normal position. Alzak reflectors are engineered to produce an asymmetric beam which provides uniform light over entire working area. Louvered fixture is of similar design but has the added protection of louvers against any possible glare from stray light. Fixtures are wired and include Levolier pull switch, ballasts and lamp starters.

For Mounting — Keyhole slots are located in back of fixture. $\frac{1}{2}$ knockouts for electrical connections are located in each end and in back at switch side.

Note — These fixtures are also available in continuous lengths. For overall lengths of longer fixtures, add additional lamp length to unit lengths shown in schedules.

Open Type Fixtures with Specular Alzak Reflectors



Finishes — Lacquer fixtures, Statuary Bronze or Aluminum Lacquer. Plated fixtures, Statuary Bronze or Satin Nickel.

CATAL	CATALOG No.		FOR LAMPS	Unit	Standard	Weight	
Lacquer Finish	Plated Finish	No.	Size	Longth		Each	
1040	1041	1	18″-15w-110v	181/4"	3	7 lbs.	
1042	1043	1	24"-20w-110v	241/4"	3	8 lbs.	
1044A	1045A	1	36"-30w-220v	361/4"	3	ll lbs.	
1044B	1045B	1	36″-30w-110 v	361/4"	3	12 lbs.	
1046A	1047A	1	48"-40w-220v	481/4"	3	14 lbs.	
1046B	1047B	1	48″-40w-110 ▼	481/4"	3	15 lbs.	

Louver Fixtures with Specular Alzak Reflectors

Finishes — Lacquer fixtures, Statuary Bronze or Aluminum Lacquer. Plated fixtures, Statuary Bronze or Satin Nickel.



CATAL	CATALOG Na.		FOR LAMPS	Unit	Standard	Weight	
Lacquer Finish	Plated Finish	No.	Size	Length	Package	Each	
1090	1091	1	18″-15w-110v	181/4"	3	$10^{1}/_{2}$ lbs.	
1092	1093	1	24″-20w-110v	241/4"	3	13 lbs.	
1094A	1095A	1 1	36″-30w-220v	361/4"	3	$17\frac{1}{2}$ lbs.	
1094B	1095 B	1 1	36″-30w-110v	361/4"	3	$18\frac{1}{2}$ lbs.	
1096A	1097A	1 1	48″-40w-220v	481/4"	3	23 lbs.	
1096B	1097B	1 1	48″-40w-110v	481/4"	3	24 lbs.	

Deal Plate Fixtures with Specular Alzak Reflectors

For use in cashiers' cages where overhead lighting cannot be employed. Reflecting surface specular Alzak, designed to light area uniformly. Wired: Toggle switch, ballasts and lamp starters included.

Deal plate fixtures can be finished in Statuary Bronze or Aluminum Lacquer. Specify color when ordering. Available in one lamp length only.



Catalog		FOR LAMPS	Length	Standard	Weight
Na.	Na.	Size		Package	Each
1085	1 1 1	18″-15w-110v	181/4"	3	7 lbs.
1086	1	24"-20w-110v	241/4"	3	9 lbs.
1087A	1 1	36"-30w-220v	361/4"	3	12 lbs.
1087B	1 1	36"-30w-110v	361/4"	3	13 lbs.

For Bank Screen and Deal Plate Lighting



Fixtures Mounted to Top Rail of Bank Cage




For Low Bank Counters
For Deal Plate Lighting




Schedule O Discounts

Lighting Pictures and Wall Displays



No. 645 or 655 Series







Typical Wall Display Lighting



PICTURE LIGHTING FIXTURES

For Fluorescent Lamps





Nos. 690 and 710 Series

Nos. 645 and 655 Series

These fixtures are designed for every required adjustment to give proper lighting. Shade is adjustable at fitting on top, horizontal arms are adjustable in or out and vertical adjustment can be made at strap fitting fastened to picture frame or ballast box.

Porcelain Enamel reflectors used in these fixtures properly diffuse the light and distribute it evenly over the entire picture without glare or highlights.

Nos. 690 and 710 series are for 18", 24" and 36" lamps. Ballasts and lamp starters are located in fixtures.

Nos. 645 and 655 series are for 18" and 36" T-8 lamps only. Ballasts are mounted behind the picture in a special ballast box which is furnished. Lamp starters are located in fixture body. All fixtures are furnished wired and include lamp starters, ballasts, cord and plug.


Finish — Steel, gold spray, brass, and brush brass. Other finishes on special order **Standard Package** — Three fixtures, may be assorted.

Note — Fixtures for 36" lamps have two supports.

Catalog No. FOR LAMPS		BODY DIMENSIONS			MAXI LENGTI	Weight			
STEEL	BRASS	No.	Size	Hgt.	Width	Length	Horiz.	Vert.	Each
690	710	1	18"-15w-110v	4"	$\begin{array}{c c} 4^{1/2''} \\ 4^{1/2''} \\ 4^{1/2''} \\ 4^{1/2''} \end{array}$	18 ¹ / ₄ "	15"	6"	10 lbs.
691	711	1	24"-20w-110v	4"		24 ¹ / ₄ "	15"	8"	12 lbs.
692A	712A	1	36"-30w-220v	4"		36 ¹ / ₄ "	18"	8"	17 lbs.
692B	712B	1	36"-30w-110v	4"		36 ¹ / ₄ "	18"	8"	18 lbs.
645	655	1 1 1	18"-15w-110v	2 ³ / ₄ "	3 ³ / ₈ "	21"	18"	24"	8 lbs.
646A	656 A		36"-30w-220v	2 ³ / ₄ "	3 ³ / ₈ "	39"	18"	24"	14 lbs.
646B	656 B		36"-30w-110v	2 ³ / ₄ "	3 ³ / ₈ "	39"	18"	24"	15 lbs.

WALL DISPLAY LIGHTING TROUGH

18", 24," 36" and 48" Fluorescent Lamps



For Continuous Installations

Continuous fixtures for one row of lamps. For lighting wall displays, rug racks, art galleries, etc. They have correctly designed specular ALZAK reflectors for proper distribution of light.

They are designed to be mounted direct to the ceiling and have mounting holes in top and 1/2'' knockouts in top and ends for electrical connections. For unusually high ceilings, suspension supports can be furnished.

Details of installation should be furnished so that proper location of fixture on ceiling can be recommended by us. This is important if correct lighting effect is to be obtained.

These fixtures are made of steel and can be finished in any standard lacquer color. Aluminum lacquer is standard and will be furnished unless otherwise specified. Wired, ballasts and lamp starters included.

	Cat. No.	No. Rows	For Lamps	Weight Per Ft.
l	2371	1	18", 24", 36", and 48"	5 lbs.

ADJUSTABLE BRACKET FIXTURES

For 18" and 24" Fluorescent Lamps

One-light units available for 18" and 24" lamps. They are shown with four different types of mountings and can be used for lighting bulletin boards, wall displays, counters, display cabinets, blackboards, filing cabinets, etc. All fixtures are furnished completely wired with ballasts, lamp starters and toggle switch. Reflecting surface Porcelain Enamel. Nos. 971 and 974 Series include cord and plug. All fixtures wired for 110-volt A.C. operation.






Nos. 940, 941, 990, 991

Nos. 970, 972, 980, 982]





Nos. 971, 973, 981, 983

Nos. 974, 975, 984, 985

Catalo	Catalog No.		FOR LAMPS		BODY SIZE			Weight
STEEL	BRASS	No.	Size	Hgt.	Width	Length	Pkg.	Each
940 941	990 991	1	18″—15w 24″—20w	31/2"	41/2"	18 ¹ / ₄ " 24 ¹ / ₄ "	1	8 lbs. 10 lbs.
970 972	980 982	1	18″—15w 24″—20w	31/2" 31/2"	41/2" 41/2"	18 ¹ / ₄ " 24 ¹ / ₄ "	1	8 lbs. 10 lbs.
971 973	981 983	1	18″—15w 24″—20w	31/2" 31/2"	41/2" 41/2"	18 ¹ / ₄ " 24 ¹ / ₄ "	1	8 lbs. 10 lbs.
974 975	984 985	1	18"—15w 24"—20w	31/2"	41/2" 41/2"	18 ¹ / ₄ " 24 ¹ / ₄ "	1	10 lbs. 12 lbs.

Finish — Steel, lacquered any standard color. Brass, any standard plated finish. Chromium on brass only; extra.

Mounting — Nos. 940, 941, 990 and 991; height 15". Base is furnished with crowfoot for fixed installation.


Nos. 970, 972, 980 and **982;** extension from wall is $8^{1}/_{2}$ " overall. Specify whether crowfoot or hickey is required when ordering.

Nos. 971, 973, 981 and **983;** horizontal extension is $8\frac{3}{4}$ " overall. Vertical support is 24". Mounting Flange has vertical adjustment.

Nos. 974, 975, 984 and **985;** horizontal extension is $8\frac{3}{4}$ " overall. Vertical support is 24" and has clamp support with vertical adjustment.

Schedule O Discounts

Utility Fixtures for Many Applications




No. 940



No. 970



No. 971




No. 974




For Wall Displays

CONTINUOUS BRACKET FIXTURES

For Fluorescent Lamps





Illustrating Continuous Bracket Fixture for Lighting Wall Map



Illustrating No. 1781 Drafting Table Fixture




Continuous fixtures for lighting wall displays, bulletin boards, filing cabinets, etc. Fixtures are furnished with sufficient number of supports to insure rigid mounting. They are wired and include ballasts and lamp starters.

Porcelain Enamel reflecting surface assures proper distribution of light.

Length — Made in lengths up to 10 feet with provisions for coupling units together for longer installations.

Basic lengths for 36" and 48" lamps with additional lengths available for 18", 24", 36" and 48" lamps.

Finish — Steel, lacquered any standard color; brass, any standard plated finish. Chromium on brass only; extra.



Illustrating Available Mounting Arrangements

Catal	na No		BASIC	LENGTH	BODY		Approx.
Culdi	Catalog No.		FOR LAMPS		DIMENSIONS		Weight
STEEL	BRASS	Length	No.	Size	Height	Width	Per Ft.
642A	652A	361/4"	1	36"-30w-220v	4"	1 41/2"	6 lbs.
642B	652B	361/4"	1	36″-30w-110v	4"	$4^{1/2}$ "	6 lbs.
643A	653A	481/4"	1	48"-40w-220v	4"	$4^{1/2}''$	6 lbs.
643B	653 B	481/4"	1	48″-40w-110v	4"	$4^{1/2}''$	6 lbs.

Mounting — Five mounting types are available as shown. When ordering specify type mounting, length of arm, length of fixture, number and size of lamps. State which arm is to have feed wires and whether hickey or crowfoot is required for mounting. Type "C" mounting is recommended for fixtures with horizontal support longer than 15".

DRAFTING TABLE FIXTURES

For 18", 24", 36" and 48" Fluorescent Lamps


Adjustable fixtures for drafting boards and tables. Exterior is finished in gray baked wrinkle enamel and reflecting surface is Porcelain Enamel.

Support is designed for both vertical and horizontal adjustment. Also swivel adjustment at clamp and top support. Special cast clamp is fastened to edge of board or table and provides vertical adjustment. Supporting bracket is set for proper distribution of light.

All fixtures are furnished wired complete with switch, ballasts, lamp starters, supports, cord and plug.

	•				
Catalog		FOR LAMPS	Length	Std.	Weight
No.	No.	Size	1 2011 3111	Pkg.	Each
1770	1	18"-15w-110v	181/4"	1	15 lbs.
1780	2	18″-15w-110v	181/4"	1	19 lbs.
1771	1	24″-20w-110v	241/4"	1	18 lbs.
1781	2	24"-20w-110v	241/4"	1	24 lbs.
1772A	1	36″-30w-220v	361/4"	1	22 lbs.
1772B	1	36″-30w-110v	361/4"	1	23 lbs.
1782A	2	36″-30w-220v	361/4"	1	29 lbs.
1782B	2	36″-30w-110v	361/4"	1	30 lbs.
1773A	1	48″-40w-220v	481/4"	1	25 lbs.
1773B	1	48″–40w–110v	481/4"	1	26 lbs.
1783A	2	48″-40w-220v	481/4"	1	33 lbs.
1783B	2	48″-40w-110v	481/4"	1	34 lbs.





11/8"

Fixtures for 18" and 24" lamps have one support and fixtures for 36" and 48" lamps have two.

LIBRARY TABLE FIXTURES

For 36" and 48" Fluorescent Lamps



Soft, glare-free illumination for restful reading is provided with these fixtures. They are listed in standard lengths for one row of lamps, for tables 6' to 12' long.

Each fixture has two supports and is furnished wired with lamp starters, ballasts and toggle switch. They have a specially designed Specular ALZAK reflector which produces uniform lighting over the entire reading area. Lamps are shielded from normal vision of persons sitting at table.


Finish — Steel, brown baked wrinkle enamel. Bronze, plated in statuary bronze or satin nickel.

Standard Package — One fixture.

CATALO	CATALOG No.		FOR LAMPS	Overall	Recommended for Length	Weight Each
STEEL	BRONZE	No.	Size	Length	Table	Each
1280A 1280B	1290 A 1290 B	1 1	48"—40w—220v 48"—40w—110v	481/4"	6' 6'	36 lbs. 37 lbs.
1281A 1281B	1291 A 1291 B	2 2	36"—30w—220v 36"—30w—110v	75 ³ / ₄ " 75 ³ / ₄ "	8' 8'	44 lbs. 44 lbs.
1282A 1282B	1292 A 1292 B	2 2	48"—40w—220v 48"—40w—110v	99 ³ / ₄ " 99 ³ / ₄ "	10' 10'	56 lbs. 56 lbs.
1283A 1283B	1293 A 1293 B	3 3	36"—30w—220v 36"—30w—110v	$\begin{array}{c c} 1 & 1 & 1 & 3/4'' \\ 1 & 1 & 1 & 3/4'' \end{array}$	12' 12'	60 lbs. 61 lbs.

CONTINUOUS SHOW WINDOW FOOTLIGHTS

For 18", 24", 36" and 48" Fluorescent Lamps



One Row Window Footlight

Two Row Window Footlight


Window footlights for one and two rows of lamps; 18", 24", 36" and 48" size. The use of these footlights will help eliminate image reflections in the window and build up intensities in lower window area.

Fixtures are made of steel and bronze in continuous lengths to fit available window space. They are **wired and include ballasts and lamp starters.**

Finish—Steel, lacquered any standard color. Bronze, any standard plated finish. Chromium on bronze only; extra.


CATAL	OG No.	No.	FOR LAMPS	Approx. Weight	
STEEL	BRONZE	Rows	FOR LAMPS	Per Ft.	
3230 3232	3231 3233	1 2	18", 24", 36" and 48" 18", 24", 36" and 48"	5 lbs. 7 lbs.	

Cool, Glareless Illumination for Easy Reading



Designed With Proper Cutoff To Shield Eyes From Glare

Add Punch and Color to Show Window Displays



Typical Window Footlight Installation





Boyd-Richardson Company, St. Louis, Missouri



The Misses Johnson Department Store, Minneapolis, Minn.



Reliable Furniture Company, Akron, Ohio



SHOW WINDOW REFLECTORS

For $18^{\prime\prime}$, $24^{\prime\prime}$, $36^{\prime\prime}$ and $48^{\prime\prime}$ Fluorescent Lamps

For Windows of Every Size and Description

These fixtures are designed for lighting all types of show windows. They are available for two, three and four: 18", 24", 36" and 48" lamps.

Fixture bodies are made of steel, finished in aluminum lacquer. Mounting holes are conveniently located for installation and 1/2" knockouts are furnished in top, ends and back for electrical connections. Ends are punched so that two or more units can be butted for continuous installations. In the event it is desirable to allow space between units and for corner connections, the 1/2" knockouts in the ends will accommodate pipe or BX.

Complete . . . Ready to Install

Fixtures are furnished complete with sockets, ballasts, lamp starters and wire lead. They are wired, ready for installation. Starting compensators are furnished with all fixtures for 36" and 48" lamps using Tulamp ballasts.

Engineered for Maximum Efficiency

The Specular ALZAK reflectors used in these fixtures are correctly engineered for most efficient lighting in show windows. They provide maximum illumination, in the correct proportions, on Zones A, B and C shown on the layouts on page 16, thus effecting a smooth, evenly lighted appearance to the entire window. See listings on page 16 for proper selection of fixtures for your particular installation.

Island Show Windows


In most cases, island show windows are treated as two shallow windows placed back to back. With this information, proper selection can be made from the information given on page 16.

Coupling Arrangement for Continuous Installations

Individual fixtures can be butted and bolted together to make a continuous fixture to fill out window length as shown here.



Recessed Fixtures



In many instances it is desirable to recess these fixtures in the ceiling. For recessing, these fixtures are furnished as illustrated above.

SHOW WINDOW REFLECTORS

For 18", 24", 36" and 48" Fluorescent Lamps

Show Window Lighting Fixtures with

ASYMMETRIC ALZAK REFLECTORS

For Lighting Medium and Deep Windows

Catalog		FOR LAMPS	D	IMENSION	15	Weight
No.	No.	Size	Length	Width	Height	Each
7218	2	18″-15w-110v	181/4"	14"	6"	21 lbs.
7224	2	24″-20w-110v	241/4"	14"	6″	24 lbs.
7236A	2	36″-30w-220v	361/4"	14"	6"	36 lbs.
7236 B	2	36″-30w-110v	361/4"	14"	6″	36 lbs.
7248A	2	48″-40w-220v	481/4"	14"	6″	42 lbs.
7248 B	2	48″-40w-110v	481/4"	14"	6″	42 lbs.
7318	3	18″-15w-110v	181/4"	20″	6″	29 lbs.
7324	3	24″-20w-110v	241/4"	20"	6"	31 lbs.
7336A	3	36″-30w-220v	361/4"	20″	6"	47 lbs.
7336 B	3	36″-30w-110v	361/4"	20″	6"	47 lbs.
7348A	3	48″-40w-220v	481/4"	20"	6"	56 lbs.
7348B	3	48″-40w-110v	481/4"	20"	6″	56 lbs.
7418	4	18″-15w-110v	181/4"	26"	61/2"	36 lbs.
7424	4	24″-20w-110v	241/4"	26"	$6^{1/2}''$	41 lbs.
7436A	4	36″-30w-220v	361/4"	26"	$6^{1/2}''$	60 lbs.
7436 B	4	36″-30w-110v	361/4"	26″	$61/\bar{2}''$	60 lbs.
7448A	4	48″-40w-220v	481/4"	26"	$6^{1/2}''$	73 lbs.
7448 B	4	48″-40w-110v	481/4"	26"	61/2''	73 lbs.

Standard Package — One fixture.


Show Window Lighting Fixtures with

SYMMETRIC ALZAH REFLECTORS

For Lighting Shallow Windows

Catalog		FOR LAMPS	D	IMENSION	ıs	Weight
No.	No.	Size	Length	ength Width		Each
9218	2	18″-15w-110v	181/4"	14"	6"	21 lbs.
9224	2	24″-20w-110v	241/4"	14"	6"	24 lbs.
9236A	2	36″-30w-220v	361/4"	14"	6"	36 lbs.
9236B	2	36″-30w-110v	361/4"	14"	6"	36 lbs.
9248A	2	48″–40w–220v	481/4"	14"	6"	42 lbs.
9248 B	2	48″-40w-110v	481/4"	14"	6"	42 lbs.
9318	3	18″-15w-110v	181/4"	20"	6"	29 lbs.
9324	3	24″-20w-110v	241/4"	20″	6"	31 lbs.
9336A	3	36″-30w-220v	361/4"	20″	6″	47 lbs.
9336 B	3	36″-30w-110v	361/4"	20″	6"	47 lbs.
9348A	3	48″-40w-220v	481/4"	20″	6"	56 lbs.
9348 B	3	48″-40w-110v	481/4"	20″	6"	56 lbs.
9418	4	18″-15w-110v	181/4"	26"	61/2"	36 lbs.
9424	4	24″-20w-110v	241/4"	26"	$6^{1/2}$ "	41 lbs.
9436A	4	36″-30w-220v	361/4"	26"	$6^{1/2}''$	60 lbs.
9436B	4	36″-30w-110v	361/4"	26"	$6^{1/2}''$	60 lbs.
9448A	4	48″-40w-220v	481/4"	26"	61/2''	73 lbs.
9448 B	4	48″-40w-110v	481/4"	26″	$6^{1/2}$ "	73 lbs.


Standard Package — One fixture.



ASYMMETRIC REFLECTOR

DISTRIBUTION CURVES

DAY-BRITE SHOW WINDOW REFLECTORS



SYMMETRIC REFLECTOR

Efficient Lighting Equipment for All Types of Show Windows



No. 7218 Series — Asymmetric Reflectors No. 9218 Series — Symmetric Reflectors




THREE-LIGHT FIXTURES

No. 7318 Series — Asymmetric Reflectors
No. 9318 Series — Symmetric Reflectors



FOUR-LIGHT FIXTURES

No. 7418 Series — Asymmetric Reflectors
No. 9418 Series — Symmetric Reflectors



Day Brite Lighting, Inc.

CORRECTLY ENGINEERED REFLECTORS FOR MAXIMUM EFFICIENCY

By using these charts, you can figure out your own requirements in window lighting. The foot-candle intensities shown here can be used as a basis from which to approximate the number and size fixtures needed for a complete installation.

Readings with Symmetric Type Reflectors for Shallow Windows

	Fixtures for Para	•	Fixtures for Para	•	Fixtures for Four Lamps Parallel	
No. Fixtures Total No. Lamps	1-No. 9236	1-No. 9248	1-No. 9336	1-No. 9348	1-No. 9436	1-No. 9448
	2-30 watt	2-40 watt	3-30 watt	3-40 watt	4-30 watt	4-40 watt
Zone A	38 fc.	55 fc.	52 fc.	75 fc.	69 fc.	100 fc.
Zone B	41 fc.	60 fc.	52 fc.	75 fc.	66 fc.	95 fc.
Zone C	95 fc.	135 fc.	145 fc.	210 fc.	155 fc.	230 fc.
No. Fixtures Total No. Lamps	2-No. 9236	2-Na, 9248	2-No. 9336	2-No. 9348	2-No. 9436	2-No. 944 8
	4-30 watt	4-40 watt	6-30 watt	6-40 watt	8-30 watt	8-40 watt
Zone A	59 fc.	85 fc.	83 fc.	120 fc.	107 fc.	155 fc.
Zone B	48 fc.	70 fc.	76 fc.	110 fc.	100 fc.	145 fc.
Zone C	97 fc.	140 fc.	166 fc.	240 fc.	173 fc.	250 fc.
No. Fixtures Total No. Lamps	3-Na. 9236	3-No. 9248	3-No. 9336	3-No. 9348	3-No. 9436	3-Na. 9448
	6-30 watt	6-40 watt	9-30 watt	9-40 watt	12-30 watt	12-40 watt
Zone A	90 fc.	110 fc.	130 fc.	155 fc.	145 fc.	210 fc.
Zone B	70 fc.	85 fc.	105 fc.	130 fc.	138 fc.	200 fc.
Zone C	120 fc.	145 fc.	210 fc.	260 fc.	186 fc.	270 fc.

Tests made with White lamps. Intensities with DAY LIGHT lamps will be approximately 15% less.

Readings with Asymmetric Reflectors for Medium Windows

		Fixtures for Para	•	Fixtures for Para		Fixtures for Four Lamps Parallel	
	No. Fixtures	1-No. 7236	1-No. 7248	1-No. 7336	1-No. 7348	1-No. 7436	1-No. 7448
	Total No. Lamps	2-30 watt	2-40 watt	3-30 watt	3-40 watt	4-30 watt	4-40 watt
	Zone A	40 fc.	55 fc.	55 fc.	75 fc.	70 fc.	100 fc.
	Zone B	25 fc.	30 fc.	35 fc.	50 fc.	50 fc.	70 fc.
	Zone C	20 fc.	25 fc.	25 fc.	35 fc.	35 fc.	50 fc.
ı	No. Fixtures Total No. Lamps	2-No. 7236 4-30 watt	2-No. 7248 4-40 watt	2-No. 7336 6-30 watt	2-No. 7348 6-40 watt	2-No. 7436 8-30 watt	2-No. 7448 8-40 watt
	Zone A	60 fc.	80 fc.	80 fc.	115 fc.	105 fc.	150 fc.
	Zone B	40 fc.	45 fc.	50 fc.	70 fc.	75 fc.	100 fc.
	Zone C	25 fc.	35 fc.	40 fc.	50 fc.	55 fc.	75 fc.
	No. Fixtures Total No. Lamps	3-No. 7236 6-30 watt	3-No. 7248 6-40 watt	3–No. 7336 9–30 watt	3-No. 7348 9-40 watt	3-No. 7436 12-30 watt	3-No. 7448 12-40 watt
	Zone A	75 fc.	100 fc.	100 fc.	145 fc.	130 fc.	185 fc.
	Zone B	45 fc.	55 fc.	70 fc.	100 fc.	100 fc.	140 fc.
	Zone C	35 fc.	45 fc.	50 fc.	70 fc.	75 fc.	105 fc.

Tests made with WHITE lamps. Intensities with DAY LIGHT lamps will be approximately 15% less.

Readings with Asymmetric Reflectors for Deep Windows

	Fixtures for Para	•	Fixtures for Para	•	Fixtures for Four Lamps Parallel	
No. Fixtures	1-Na. 7236	1-No, 7248	1-No. 7336	1-No. 7348	1-No. 7436	1-No. 7448
Total No. Lamps	2-30 watt	2-40 watt	3-30 watt	3-40 watt	4-30 watt	4-40 watt
Zone A	40 fc.	55 fc.	55 fc.	75 fc.	70 fc.	100 fc.
Zone B	35 fc.	50 fc.	60 fc.	80 fc.	80 fc.	100 fc.
Zone C	30 fc.	40 fc.	4 5 fc.	60 fc.	60 fc.	80 fc.
No. Fixtures	2-No. 7236	2–No. 7248	2-No. 7336	2-No. 7348	2-No. 7436	2-No. 7448
Total No. Lamps	4-30 watt	4–40 watt	6-30 watt	6-40 watt	8-30 watt	8-40 watt
Zone A	60 fc.	80 fc.	80 fc.	115 fc.	105 fc.	150 fc.
Zone B	55 fc.	75 fc.	85 fc.	120 fc.	115 fc.	160 fc.
Zone C	40 fc.	55 fc.	65 fc.	90 fc.	85 fc.	120 fc.
No. Fixtures Total No. Lamps	3-No. 7236	3-No. 7248	3-No. 7336	3-No. 7348	3-No. 7436	3-No. 7448
	6-30 watt	6-40 watt	9-30 watt	9-40 watt	12-30 watt	12-40 watt
Zone A	75 fc.	100 fc.	100 fc.	145 fc.	130 fc.	185 fc.
Zone B	70 fc.	95 fc.	105 fc.	150 fc.	140 fc.	200 fc.
Zone C	45 fc.	65 fc.	80 fc.	110 fc.	105 fc.	150 fc.


Tests made with WHITE lamps. Intensities with DAY LIGHT lamps will be approximately 15% less.


Correctly proportioned intensities are provided on Zones A, B and C, thus providing plenty of light throughout the entire window.

Since there is naturally considerable variation in show window sizes, we have chosen three typical layouts that represent the general average for the purpose of setting up and testing this equipment.

Tests made after lamps had been in use 100 hours.










DECORATIVE SURFACE FIXTURES

For 18", 24", 36" and 48" Fluorescent Lamps





These smart looking surface fixtures have many uses for general lighting and decorative lighting effects. The wide variety of colors available in Fluorescent lamps makes them especially effective for use on walls and ceilings, in lobbies, tap rooms, taverns, reception rooms, etc.


Fixtures are finished in polished chromium and are fastened to ceiling or wall through mounting holes in back plate. 1/2'' knockouts are provided for electrical connections. They are wired and include ballasts and lamp starters.

		500 111100			
Catalog	No.	FOR LAMPS	Overall	Standard	Weight
No.		Size	Length	Package	Each
2118	1	18"—15w—110v		3	6 lbs.
2218	2	18"—15w—110v		1	7 lbs.
2318	3	18"—15w—110v		1	9 lbs.
2124	1	24"—20w—110v	26"	3	7 lbs.
2224	2	24"—20w—110v	26"	1	9 lbs.
2324	3	24"—20w—110v	26"	1	11 lbs.
2136A	1	36"—30w—220v	38"	2	8 lbs.
2136B	1	36"—30w—110v	38"	2	9 lbs.
2236A	2	36"—30w—220v	38"	1	12 lbs.
2236B	2	36"—30w—110v	38"	1	13 lbs.
2336A	3	36"—30w—220v	38"	1	13 lbs.
2336B	3	36"—30w—110v	38"	1	14 lbs.
2148A	1	48"—40w—220v	50"	2	10 lbs.
2148B	1	48"—40w—110v	50"	2	11 lbs.
2248A	2	48"—40w—220v	50"	1	15 lbs.
2248B	2	48"—40w—110v	50"	1	16 lbs.
2348A	3	48"—40w—220v	50"	1	17 lbs.
2348B	3	48"—40w—110v	50"	1	18 lbs.

90° MITERED CORNER BLOCKS

To be used in connection with the above fixtures to form various designs in squares, oblongs, etc., as illustrated here.

Cat. No.	For No. Rows	Std. Pkg.	Weight, Ea.
2115	1	4	l lbs.
2215	2	4	2 lbs.
2315	3	4	3 lbs



Schedule S Discounts




For Bathrooms

For Dressing Tables





For Low Ceiling Mounting



Suggested Ceiling Treatment
Illustrating Mitered Corner Blocks



For Bathrooms and Dressing Rooms


One-light fixtures have excellent applications over or on each side of bath room or dressing room mirrors. The can be furnished with switch and convenience receptacle as hown above




ST. LOUIS, MISSOURI

CONTINUOUS COVE LIGHTING FIXTURES

For 18", 24", 36 and 48" Fluorescent Lamps



Nos. 1270, 1271



Nos. 1272, 1273

Nos. 1278, 1279

For small rooms, lobbies, taverns, reception halls, etc., these cove reflectors provide an efficient lighting system. Illustrated above are fixtures for both exposed and concealed mounting. They are available with porcelain enamel or specular Alzak reflectors, as listed.

Fixtures are designed as small as possible to accommodate ballasts. Other exposed shapes can be furnished to meet special architectural requirements. Full details will be furnished on request.

Lengths — Fixtures are made in single lengths up to 10', with provisions for coupling sections together for continuous installations. Junction boxes are furnished in each end of fixture for electrical connection. Furnished wired, ballasts and lamp starters are included.

Finish — Fixtures Nos. 1270, 1271, 1278 and 1279 in aluminum lacquer. Nos. 1272 and 1273 in any standard lacquer color. Specify color when ordering.

With Porcel	ain Reflector	With Alzo	ık Reflector	For Lamps	
Catalog No.	Weight Per Ft.	Catalog No.	Weight Per Ft.	ror comps	
1270 1272 1278	5 lbs. 6 lbs. 6 lbs.	1271 1273 1279	4 lbs. 5 lbs. 5 lbs.	18", 24", 36", and 48" 18", 24", 36", and 48" 18", 24", 36", and 48"	



Typical Cove Lighting Installation Rahr Malting Co., Manitowoc, Wisc.

CORNICE LIGHTING FIXTURES

For 18", 24" and 48" Fluorescent Lamps




These cornice lighting units for various lighting and decorative effects are available for one and two lamps; 18'', 24'' and 48'' size. Many applications present themselves for the use of these fixtures in lobbies, tap rooms, taverns, reception rooms, etc. They are easily installed. Have mounting holes and $\frac{1}{2}''$ knockout in back for installation and electrical connection.


Finish — These units are listed in two finishes, polished chromium and satin chromium, see schedule below.

Standard Package — Three fixtures, may be assorted.

Standard Package — Three fixtures, may be assorted.

Levolier pull switch in end is available. Specify when ordering. Fixtures wired, ballasts and lamp starters are included.






Cornice Lighting Fixtures for Back Bar Illumination




ST. LOUIS, MISSOURI

INDIRECT LIGHTING TROUGHS

For Fluorescent Lamps



No. 806 - Two Row No. 800 - One Row



No. 810 - Four Row

Indirect lighting troughs are manufactured in steel and can be furnished in any standard lacquer color. They are available in any length and can also be made with miters to form angles and squares.

All fixtures are equipped with **porcelain enameled reflectors** for permanent efficiency... to eliminate high lights and spots... and to insure perfect diffusion which is so desirable in fixtures of this type. Day-Brite porcelain enamel has a reflection factor of from 78 to 82%, is easy to maintain and will not depreciate.

Hangers and Equipment — All fixtures are furnished wired, ballasts and lamp starters included. They are complete with hangers of necessary lengths and canopies designed to match fixtures. If special spacing of hangers is required specify when ordering.

Catalog	No.	For Lamps	Approx. Wt.
Na.	Raws		Per Ft.
800	1 2	24", 36" and 48"	8 lbs.
806		24", 36" and 48"	11 lbs.
802	1 2	24", 36" and 48"	10 lbs.
808		24", 36" and 48"	14 lbs.
810	4	24", 36" and 48"	15 lbs.

Other designs in steel, bronze, aluminum and in extruded metals can be furnished. Send complete details and we will gladly furnish information and prices.

No. 808 - Two Row No. 802 - One Row

A Typical Day-Brite
Indirect Trough Installation
in the
Women's Lounge
of the
Public Service Building
Milwaukee, Wisc.





PARALUME

COMBINING EFFICIENCY AND BEAUTY FOR THE ULTIMATE IN LIGHTING

T. M. Reg. U. S. Pat. Off. Design Patented



Illustrating Two, Three and Four-Light Fixtures

For 24" and 48" Fluorescent Lamps

The Day-Brite **PARALUME** . . . designed specifically for general lighting in all types of commercial installations. Maximum wide-spread downward illumination is provided for lighting merchandise displays, counters, or desks with sufficient upward and outward lighting to give a smooth glare-free overall effect. Its sleek flowing lines make it applicable to all types of installations involving modern architectural treatments.

CEILIN	G TYPE		FOR LAMPS	BODY	DIMENSI	SNC	C. 1	
Satin Chromium Cat. No.	Boked Enomel Cat. No.	No.	Size	Length	Width	Depth	Std. Pkg.	Weight Each
6224 6248 A 6248 B	8224 8248 A 8248 B	2 2 2	24"-20w-110v 48"-40w-220v 48"-40w-110v	28" 52" 52"	91/2" 91/2" 91/2"	31/2" 31/2" 31/2"	1 1 1	17 lbs. 29 lbs. 29 lbs.
6324 6348 A 6348 B	8324 8348 A 8348 B	3 3 3	24"-20w-110v 48"-40w-220v 48"-40w-110v	28" 52" 52"	$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	4 ¹ / ₄ " 4 ¹ / ₄ " 4 ¹ / ₄ "	1 1 1	21 lbs. 36 lbs. 37 lbs.
6424 6448 A 6448 B	8424 8448 A 8448 B	4 4 4	24"-20w-110v 48"-40w-220v 48"-40w-110v	28 ³ / ₄ " 52 ³ / ₄ " 52 ³ / ₄ "	13 ¹ / ₄ " 13 ¹ / ₄ " 13 ¹ / ₄ "	$5^{1/2}''$	1 1 1	27 lbs. 45 lbs. 45 lbs.
6548A* 6548B* 6648A*	8548A* 8548B* 8648A*	4 4 6	48"-40w-220v 48"-40w-110v 48"-40w-220v	100" 100" 100"	9 ¹ / ₂ " 9 ¹ / ₂ " 11 ¹ / ₂ "	31/2" 31/2" 41/4"	1 1 1	81 lbs. 81 lbs. 85 lbs.
6648 B * 6748 A * 6748 B *	8648B* 8748A* 8748B*	8 8	48″-40w-110v 48″-40w-220v 48″-40w-110v	100" 100 ³ / ₄ " 100 ³ / ₄ "	11 ¹ / ₂ " 13 ¹ / ₄ " 13 ¹ / ₄ "		1 1 1	85 lbs. 95 lbs. 95 lbs.

With the **PARALUME** lighting intensities can be increased over present lighting systems and, in addition, the Fluorescent lamp for like intensities produces considerably less radiant heat which will materially affect room temperatures.

These fixtures are available for 24" 20-watt and 48" 40-watt lamps in three different sizes as listed in schedule. They are listed for direct ceiling mounting but if desired can be furnished with decorative hangers for suspension. See Page 21.

Standard stock fixtures for immediate shipment are manufactured in one lamp length only. However, fixtures two lamp lengths long, for 48" 40-watt lamps, can be furnished on special order. They are listed in the schedule.

*These fixtures are two lamp-lengths long and are furnished on special order only. For suspension mounting they require two sets of hangers.

NOTE—Hangers additional, See Page 21.


These fixtures can also be furnished in continuous lengths... See price list.

PARALUME



For direct ceiling mounting the **PARALUME** is arranged for easy installation. Bead chain is applied after the ceiling plate, complete with all control equipment and sockets has been installed and connections made. The fixture body is supported by the chain while it is being fastened in place.

Control Equipment — Fixtures are furnished wired, ready to install. They include sockets, lamp starters and ballasts. Tulamp ballasts are used in all fixtures for 2, 4, 6 and 8 lamps. Three-lamp fixtures include one Tulamp and one one-lamp ballast. Starting compensators are furnished with all fixtures for 48" 40-watt lamps.



Hangers for Suspension Mounting

Complete hangers for suspension mounting include two stems, a decorative canopy (with removable back plate for easy installation) and all necessary fittings for complete installation.

No. 866 . . . Satin Chromium Finish No. 866 . . . Baked Aluminum Finish

Overall length of fixture and hanger, 36". Shipping weight, 8 lbs.

Finishes (Fixture Body) — Available in two finishes, Satin Chromium and White Baked Enamel. Cast ends on both types are satin finish with polished ornament. White sockets furnished with White fixtures, Black sockets with Chromium fixtures.


Engineered for High Level Illumination

Typical distribution curve for the *PARALUME* is shown at right. Note wide-spread distribution.

The schedule below shows approximate foot-candle intensities produced in a typical installation of these fixtures under average conditions. Tests were made with White lamps after 100 hours burning. With Daylight lamps intensities will be approximately 15% less. Fixtures used were white baked enamel units for three 40-watt lamps each. Intensities for other size units will be in proportion.

		FIXTURE SPACINGS										
Mounting	8' x 8'		10' x 10'		12' x 12'		14' x 14'					
Heights	Two Rows of Units			Four Rows of Units								
	APPROXI	MATE FOO	T-CANDLE I	INTENSITIES	UNDER AV	ERAGE CO	NDITIONS*					
8 feet 10 feet 12 feet 14 feet	44—52 40—47 38—43 34—39	50—60 48—55 46—52 44—50	30—34 28—32 26—30 24—28	34—40 32—38 30—36 28—34	21—24 20—23 19—22 18—21	24—28 22—26 21—25 20—24	14—17 14—17 13—16 13—16	17—20 17—20 16—19 16—19				

*Taken at working level, 30" above floor.





TYPICAL DISTRIBUTION CURVE

With Specular Alzak Reflectors

COMMERCIAL UNITS

For 24" and 48" Fluorescent Lamps





Complete Hangers Can Be Furnished for Suspension Mounting



Keedoozle Store, Memphis, Tenn.



ST. LOUIS, MISSOURI

ILLUSTRATING No. 3571


These fixtures are manufactured for four and five lamps only and are available for 24" 20-watt and 48" 40-watt sizes. They have been engineered to produce general lighting of highest efficiency. Individual, correctly designed ALZAK reflectors are located behind each lamp.

Due to the efficiency of these fixtures, they can be mounted on high ceilings without hangers and will provide high intensity lighting on working areas. If desired, these fixtures can be suspended and the end lamps will provide sufficient upward lighting to eliminate dark spots and shadows on the ceiling.

Finish — Reflectors, Specular ALZAK; cross straps, baked aluminum enamel. Cast ornamental ends of body, satin and polished aluminum.

Control Equipment — All fixtures are wired, ready to install, and include sockets, ballasts and lamp starters. Starting compensators are furnished with units for 48" 40-watt lamps.

Hangers — Catalog No. 866. Shipping Weight 8Lbs. Complete hangers for suspension mounting include two stems, and a decorative canopy and all necessary fittings for complete installation.




Distribution Curve

Catalog		For Lamps		Dimension	s	Std.	Weight
No.	No.	Size	Height	Width	Length	Pkg.	Each
3570 3590	4 5	24"-20w-110v 24"-20w-110v	6 ³ / ₄ " 8 ¹ / ₂ "	121/2"	26 ¹ / ₂ " 26 ¹ / ₂ "	1	25 lbs. 28 lbs.
3571A	4	48"-40w-220v	$\frac{6^{3/2}}{6^{3/4}}$	$\frac{13/4}{12!/2''}$	501/2"	1	43 lbs.
3571B 3591A	4 5	48″-40w-110v 48″-40w-220v	6 ³ / ₄ " 8 ¹ / ₂ "	$12^{1/2''}$ $15^{1/4''}$	$50^{1/2}$ " $50^{1/2}$ "	1	43 lbs. 53 lbs.
3591B	5	48″-40w-110v	81/2"	151/4"	501/2"	i	54 lbs.

COFFER FIXTURES

For Fluorescent Lamps

BUILT-IN ARCHITECTURAL ELEMENTS . . . FOR GENERAL LIGHTING



RECESSED TYPE WITH GLASS

RECESSED TYPE OPEN

These coffer fixtures can be applied in many ways for smart modern lighting effects in stores, offices, public buildings, etc.

They are manufactured in single units as listed in schedule below. Two styles are available — Open Type, and with Silverite glass panels in continuous hinged frames. Steel frames are finished in baked white or aluminum enamel (specify color) and bronze frames in polished chromium plated finish. Roughing boxes are galvanized iron with knockouts conveniently located for electrical connections. Reflectors in Glass Panel units are Specular ALZAK and in Open Type units are baked white enamel.

All fixtures are wired, lamp starters and ballasts included. Standard Package — One fixture.

Note — Plaster Frames are available, see detail above.

Catalo			FOR LAMPS	В	OX SIZ	E	Approx.	DI .			
STEEL Frame Baked Finish	BRONZE Frame Chromium Finish	No.	Size	Length	Width	Depth	Weight Each Lbs.	Plaster Frame No.			
	Fixtures with Silverite Glass Panels										
\$\begin{array}{c c c c c c c c c c c c c c c c c c c					117/8" 117/8" 117/8" 117/8" 117/8" 117/8" 117/8" 117/8" 117/8"	8″	30 50 50 60 60 100 120 120	5660 5661 5661 5662 5662 5663 5663 5664			
		ne-Li	ght Fixtures wi								
\$5918 \$5924 \$5936B \$5948B	C5918 C5924 C5936B C5948B	1 1 1 1	18"-15w-110v 24"-20w-110v 36"-30w-110v 48"-40w-110v	18 ¹ / ₄ " 24 ¹ / ₄ " 36 ¹ / ₄ " 48 ¹ / ₄ "	6" 6" 6"	4" 4" 4" 4"	14 19 24 30	• • • •			
			Cpen Type	Fixtur	es						
\$5724 \$5725A \$5725B \$5726A \$5726B \$5727A \$5727B	C5724 C5725A C5725B C5726A C5726B C5727A C5727B	2 2 14 14 14 *4 *4	24"-20w-110v 48"-40w-220v 48"-40w-110v 48"-40w-220v 48"-40w-110v 48"-40w-220v 48"-40w-110v	24 ¹ / ₄ " 48 ¹ / ₄ " 96 ¹ / ₄ " 96 ¹ / ₄ " 48 ¹ / ₄ "	117/8" 117/8" 117/8" 117/8" 117/8" 213/8" 213/8"	10" 10" 10" 10" 10" 10"	25 50 50 100 100 100	5670 5671 5671 5672 5672 5673 5673			

†These fixtures are two lamp-lengths long. *These fixtures are for four lamps parallel.



Stix, Baer & Fuller, St. Louis, Missouri

Day Brite
Lighting, Inc.


ST. LOUIS, MISSOURI

Schedule O Discounts

Two Types of Reflectors Are Available... Specular Alzak and White Baked Enamel


RECESSED LOUVER FIXTURES

For 24", 36" and 48" Fluorescent Lamps





FIXTURE WITH WHITE BAKED ENAMEL REFLECTOR



FIXTURE WITH ALZAK REFLECTOR



Recessed louver fixtures for smart, modern lighting effects in stores, offices, public buildings, etc.

They are manufactured in single units as listed in schedule below. Two types of reflectors are available — Specular ALZAK and white baked enamel. Louvers are finished in white or aluminum baked enamel (specify color) and are removable for easy access to interior of fixture.

Ceiling frames are heavy gauge die-rolled zee-bar shape.

Steel frames are finished in baked white or aluminum enamel (specify color). Roughing boxes are galvanized iron with knockouts conveniently located for electrical connections.

All fixtures are wired, lamp starters and ballasts included. Standard Package — One fixture.

Note — Plaster Frames are available; see details page 23.

CATALOG		FOR LAMPS		BOX SIZE		Approx. Weight	Plaster Frame			
No.	No.	No. Size		Length Width		Each Lbs.	No.			
Fixtures with Specular Alzak Reflectors										
S5824X	2	24″-20w-110v	241/4"	117/8"	8″	30	5660			
S5825AX S5825BX	2 2	36"-30w-220v 36"-30w-110v	36 ¹ / ₄ " 36 ¹ / ₄ "	$11\frac{7}{8}$ " $11\frac{7}{8}$ "	8″ 8″	44 44	5661 5661			
S5826AX	2	48"-40w-220v	481/4"	$ 11\frac{7}{8}''$	8"	53	5662			
S5826BX S5827AX	2 *4	48"-40w-110v 36"-30w-220v	48 ¹ / ₄ " 72 ¹ / ₄ "	$11\frac{7}{8}$ " $11\frac{7}{8}$ "	8" 8"	53 82	5662 5663			
S5827BX	*4	36"-30w-110v	721/4"	$11\frac{7}{8}''$	8″	82	5663			
\$5828AX \$5828BX	*4 *4	48"-40w-220v 48"-40w-110v	96 ¹ / ₄ " 96 ¹ / ₄ "	$11\frac{7}{8}$ " $11\frac{7}{8}$ "	8" 8"	100 100	5664 5664			
Fixtu	res v	vith White Bak	ed Ena	mel Ref	lector	s				
S5824Z S5825AZ	2	24"-20w-110v 36"-30w-220v	24 ¹ / ₄ " 36 ¹ / ₄ "	117/8"	8″ 8″	32 48	5660 5661			
S5825BZ	2	36″-30w-110v	361/4"	$11\frac{7}{8}''$	8″	48	5661			
\$5826AZ \$5826BZ	2 2 2 2	48″-40w-220v 48″-40w-110v	48 ¹ / ₄ " 48 ¹ / ₄ "	$11\frac{7}{8}$ " $11\frac{7}{8}$ "	8″ 8″	58 58	5662 5662			
S5827AZ	*4	36″-30w-220v	721/4"	$11^{\frac{7}{8}}$ "	8″	90	5663			
\$5827 BZ \$5828 AZ	*4 *4	36"-30w-110v 48"-40w-220v	72 ¹ / ₄ " 96 ¹ / ₄ "	$11\frac{7}{8}''$ $11\frac{7}{8}''$	8" 8"	90 110	5663 5664			
S5828BZ	*4	48"-40w-110v	961/4"	$ 11\frac{7}{8}$ "	8"	110	5664			


^{*} These fixtures are two lamp-lengths long.

CEILING LUMINAIRES

For 24", 36" and 48" Fluorescent Lamps

Schedule O Discounts

With Specular Alzak Reflectors



Illustrating Two, Three and Four-Light Fixtures

Shallow ceiling units designed for use in lobbies, reception halls, public buildings, stores and similar places. The bodies are made of steel and are supplied in any standard lacquer color. Reflectors are Specular Alzak and are designed for wide-spread illumination. Fixtures are fastened to ceiling through mounting holes in back plate. Knockouts are provided for electrical connections.

These fixtures are available in units for two, three and four rows of lamps — 24" 20-watt, 36" 30-watt and 48" 40-watt size.

All fixtures are furnished completely wired with sockets, lamp starters and ballasts, ready for installation.

Catalog]	FOR LAMPS		DIMENSIONS		Weight
No.	No.	Size	Height	Width	Length	Each
5224 5324 5424	3 4	24"—20w—110v 24"—20w—110v 24"—20w—110v	4 ¹ / ₂ " 4 ¹ / ₂ " 4 ¹ / ₂ "	12½" 16" 19½"	24 ¹ / ₄ " 24 ¹ / ₄ " 24 ¹ / ₄ "	16 lbs. 18 lbs. 20 lbs.
5236A 5236B 5336A 5336B 5436A 5436B	2 2 3 3 4 4 4	36"—30w—220v 36"—30w—110v 36"—30w—220v 36"—30w—110v 36"—30w—220v 36"—30w—110v	4 ¹ / ₂ " 4 ¹ / ₂ " 4 ¹ / ₂ " 4 ¹ / ₂ " 4 ¹ / ₂ "	12 ¹ / ₂ " 12 ¹ / ₂ " 16" 16" 19 ¹ / ₂ "	36 ¹ / ₄ " 36 ¹ / ₄ " 36 ¹ / ₄ " 36 ¹ / ₄ " 36 ¹ / ₄ "	24 lbs. 24 lbs. 27 lbs. 28 lbs. 30 lbs. 30 lbs.
5248A 5248B 5348A 5348B 5448A 5448B	2 2 3 3 4 4	48"—40w—220v 48"—40w—110v 48"—40w—220v 48"—40w—110v 48"—40w—220v 48"—40w—110v	4 ¹ / ₂ " 4 ¹ / ₂ " 4 ¹ / ₂ " 4 ¹ / ₂ " 4 ¹ / ₂ "	12 ¹ / ₂ " 12 ¹ / ₂ " 16" 16" 19 ¹ / ₂ " 19 ¹ / ₂ "	48 ¹ / ₄ " 48 ¹ / ₄ " 48 ¹ / ₄ " 48 ¹ / ₄ " 48 ¹ / ₄ "	32 lbs. 32 lbs. 36 lbs. 37 lbs. 40 lbs. 40 lbs.







FOR TWO 48"-40 WATT FLUORESCENT LAMPS

Better Seeing . . . For Better Production

The "TWO-FORTY" wipes out all harsh shadows . . . eliminates eye strain . . . reduces spoilage and rejects . . . and provides ideal seeing conditions for all types of work.


Open ends provide wider distribution of light with sufficient upward illumination to minimize glare. Also making the fixture easier to clean.

Complete . . . Ready to Install

The "TWO-FORTY" is completely wired with Tulamp ballast, starting compensator, lamp starters, heavy duty 6-ft. rubber-covered cord and plug. Can also be furnished without cord and plug and unwired. See listing in schedule. It is arranged for either pipe or chain suspension and the reflector is hinged for easy access to interior of fixture. Simply hang it up, install the lamps and plug it in.

With Porcelain Enameled Reflector...Permanent Efficiency...Easy to Clean

TWO TYPICAL "TWO-FORTY" INSTALLATIONS



In a Modern Bakery



In a Large Textile Mill

"TWO-FORTY" SPECIFICATIONS

Porcelain Enameled Reflector — Made in one piece and accommodates two 40-watt lamps. Day-Brite porcelain enamel has a reflection factor of from 78 to 82% and provides a permanent, highly efficient diffuse reflecting surface.

Outside Finish — Outside of fixture is light gray porcelain enamel. Hood of fixture finished in light gray baked enamel.

Switch Knockout — A $\frac{3}{8}$ " knockout is provided in both sides of hood for installation of pull-chain switch. Switch is not included.

Wiring and Control Equipment — The "TWO-FORTY" is completely wired with sockets, lamp starters, starting compensator, 6-foot heavy-duty 3-wire rubber-covered cord, plug and high power-factor Tulamp ballast for either 110-125, 199-216, or 220-250 volt A. C. operation. Fixtures can also be furnished wired without cord and plug and unwired. See schedule.

Total Wattage — Lamps and ballast consume approximately 100 watts.

Standard Package — One fixture packed in individual carton.

	FOR LAWRE	CATALOG NUMBERS				IA ENICION	ıc		
FOR LAMPS		UNWIRED	WIRED WIRED		DIMENSIONS			Approx.	Shipping
No.	Size	Without Cord ond Plug—Otherwise Complete	Without Cord ond Plug	With Cord and Plug	Height Wldth Length		Length	Power- Factor	Weight
2 2 2	48"—40w—110-125v 48"—40w—199-216v 48"—40w—220-250v	240B 240C 240A	240BW 240CW 240AW	240BX 240CX 240AX	7 ³ / ₄ " 7 ³ / ₄ " 7 ³ / ₄ "	13 ¹ / ₂ " 13 ¹ / ₂ " 13 ¹ / ₂ "	52" 52" 52"	95–100 95–100 95–100	31 lbs. 31 lbs. 31 lbs.

Note — Nos. 240C, 240CW, 240CX available on special order only.



THE "TWO-FORTY" IS EASY TO INSTALL AND MAINTAIN

For Chain Suspension — Two detachable mounting brackets are provided in top of fixture.

For Pipe Suspension — Two 1/2'' knockouts are located in top of fixture hood on 36'' centers for installing 1/2'' iron pipe hangers. If pipe hangers are used, the cord and plug is not necessary.

Hinged Top — By simply removing two screws, fixture can be swung open and is rigidly supported by three stout hinges. All parts are easily accessible for replacement or for making wire connections.


Note — Chain or Pipe hangers are not included.

LIGHTING DATA ON THE "TWO-FORTY"

The table of foot-candle intensities shown below has been prepared as an aid in determining the lighting results obtained with the "TWO-FORTY", using both Daylight and White Fluorescent lamps, based on

average conditions. Mounting heights shown are distances above floor and foot-candle readings are taken on the working plane 30" above the floor after lamps have been in use 100 hours.

			Average Foot-Candle Intensities Under Average Conditions						
Approximate Spocing	Mounting Height	o l w/iii		te Lamps	With Daylight Lamps				
оросинд	.,	J	Two Rows of Units	Four Rows of Units	Two Rows of Units	Four Rows of Units			
7' x 7' 8' x 8' 9' x 9' 10' x 10' 11' x 11' 12' x 12'	10' 10' 10' 10' 10'	49' 64' 81' 100' 121' 144'	44 36 30 25 20 16	50 42 35 29 23 18	35 30 25 21 17	42 36 30 25 19			




For Localized Lighting — Single units mounted 42" above the working plane will provide from 40 to 70 foot-candles. If units are mounted continuous, end to end, over long benches, they will provide from 70 to 95 foot-candles.

For Inspection, Color-Matching, Production, etc.


INSPECTION FIXTURES

For 18", 24", 36" and 48" Fluorescent Lamps
With Porcelain Enamel and Specular Alzak Reflectors



One-Light


Typical Distribution Curves



Specular Alzak Reflector

Porcelain Enamel Reflector

Stem and Chain Hangers



No. 1620 — Stem Hanger, lacquered (3 ft. long). One required for each fixture.

No. 1621 — Chain Hanger, lacquered (3 ft. long).
Two required for each fixture.



Two-Light


Three-Light

Many applications will be found for these inspection fixtures for lighting production lines, inspection benches, assembly benches, composing stones, type cases, laboratories, grading tables, tailoring shops and countless other industrial locations where color-matching or daylight quality illumination is required.

These fixtures are finished in machinery gray baked wrinkle enamel and are available with porcelain enamel or specular ALZAK reflectors. Distribution curves of these two types of reflectors are shown at left.

All fixtures are furnished wired and are complete with ballasts, two hooks at top for mounting, switch, cord and plug.

A 1/2'' pipe flange at top center of fixture in place of hooks is optional. If desired in this manner, specify when ordering. Cord and plug will be omitted and an 8-foot wire lead will be extended through flange.





	orcelain Reflectors		peculor leflectors		For Lamps	Body	Std.
Cat. No.	Weight Each	Cot. No.	Weight Each	No.	Size	Length	Pkg.
1640 1650 1660	13 lbs. 17 lbs. 21 lbs.	1645 1655 1665	13 lbs. 16 lbs. 20 lbs.	1 2 3	18"-15w-110v 18"-15w-110v 18"-15w-110v	18 ¹ / ₄ " 18 ¹ / ₄ " 18 ¹ / ₄ "	1 1 1
1641 1651 1661	16 lbs. 22 lbs. 25 lbs.	1646 1656 1666	16 lbs. 21 lbs. 23 lbs.	1 2 3	24"-20w-110v 24"-20w-110v 24"-20w-110v	24 ¹ / ₄ " 24 ¹ / ₄ " 24 ¹ / ₄ "	1 1 1
1642A 1642B 1652A 1652B 1662A 1662B	20 lbs. 21 lbs. 28 lbs. 28 lbs. 33 lbs. 34 lbs.	1647A 1647B 1657A 1657B 1667A 1667B	19 lbs. 20 lbs. 26 lbs. 26 lbs. 31 lbs. 32 lbs.	1 1 2 2 3 3	36"-30w-220v 36"-30w-110v 36"-30w-220v 36"-30w-110v 36"-30w-220v 36"-30w-110v	36 ¹ / ₄ " 36 ¹ / ₄ " 36 ¹ / ₄ " 36 ¹ / ₄ " 36 ¹ / ₄ "	1 1 1 1 1
1643A 1643B 1653A 1653B 1663A 1663B	27 lbs. 28 lbs. 38 lbs. 38 lbs. 41 lbs. 42 lbs.	1648A 1648B 1658A 1658B 1668A 1668B	27 lbs. 27 lbs. 36 lbs. 36 lbs. 38 lbs. 39 lbs.	1 1 2 2 3 3	48"-40w-220v 48"-40w-110v 48"-40w-220v 48"-40w-110v 48"-40w-220v 48"-40w-110v	48 ¹ / ₄ " 48 ¹ / ₄ "	

FLUORESCENT LIGHT STRIP

For 18", 24", 36" and 48" Fluorescent Lamps

A complete strip lighting system for 18", 24", 36", and 48" lamps. Available for single and double row installations. This system has many applications for illuminating coves, niches, luminous panels and for decorative lighting of all kinds. Also for exposed mounting on ceilings for general illumination.





Complete Assembly of Small Channel (No. 8800X) for One-Lamp Ballasts

Complete Assembly of Large Channel (No. 4800) for Tulamp Ballasts for Single and Double Rows of Lamps

Complete Fixtures for one lamp or any number of lamps that may be required for a continuous installation can be easily assembled from parts listed on the following pages. The No. 8800X Channel accommodates any of the control units now being manufactured for use with fluorescent lamps, except Tulamp ballasts for 30- and 40-watt lamps. For installations involving the use of the Tulamp ballasts No. 4800 Channel is listed complete with Channel Covers, Reflectors, and Fittings on page 32. Both types of channel are furnished in standard 12' lengths. However, they can be furnished in cut sections, see listing on page 34. Mounting holes and ½" knockouts are located in back of channel.

Snap-On Channel Covers for use with No. 8800X and No. 4800 Channel are available in baked aluminum enamel, porcelain enamel and polished chromium finishes. Asymmetric and Symmetric reflectors are listed in porcelain enamel and specular Alzak for use with both one-light and two-light channel.

All Channel Covers are punched for mounting sockets and lamp starters. Reflectors can be installed after covers and channel have been assembled.

Ballast Clamps are listed for use with both types of channel. Two of these clamps are required for each ballast used.

Blank Capping is available for both types of channel and is furnished in 18" lengths to be cut as required for filling in on channel where lamps are not employed.

A complete installation includes — (1) Channel, (2) Snap-On Channel Covers, (3) Ballast Clamps, (4) Service Box or End Caps, and (5) Coupling if installation is over 12' long. Asymmetric and Symmetric reflectors in porcelain enamel or specular Alzak and Cast Aluminum Ornamental End Plates can be applied if required.

Schedule S Discounts

General information pertaining to installation and details of Day-Brite Fluorescent Light Strip that is listed on the following pages.


Easily Assembled . . . Few Parts
No Small Bothersome Fittings



Punch out 1/2" knockout as required or electrical connection. Fasten Channel securely with screws, expansion shields, toggle bolts, etc.



Install Service Box and End Caps. They can be bolted direct to Channel before installation if desired.



Install Ballasts in Channel by means of Ballast Clamps. Connect wire leads to sockets and line (instructions given on Ballast housing). Fasten sockets to Channel Covers (screws are included with sockets for this purpose).




Snap Channel Covers into place by pressing firmly on top. Install lamps and installation is complete.



For installations over 12' in length couplings are required.




Schedule S Discounts



Illustrating Complete Installation
• FOR ONE-LAMP BALLASTS •













Snap-On Channel Covers



No. 8810 Series
BAKED ALUMINUM FINISH
No. 8820 Series
PORCELAIN ENAMEL FINISH
No. 8830 Series
POLISHED CHROMIUM FINISH



FLUORESCENT LIGHT STRIP

No. 8800X Series - FOR ONE ROW OF LAMPS

Channel, Fittings and Snap-on Channel Covers for 18", 24", 36" and 48" Fluorescent Lamps

UNWIRED

A complete installation includes (1) Channel, (2) Channel Covers (size and number depends upon lamps used), (3) Ballast Clamps, (4) Service Box or End Cap and (5) Coupling if installation is over 12' long. Asymmetric and Symmetric reflectors in porcelain enamel or specular Alzak can be applied if required. These reflectors are listed on page 31.

CHANNEL AND FITTINGS

Catalog	DESCRIPTION	Standard	Package
No.	DESCRIPTION	Quantity	Weight
8800X	Channel Only: (12' lengths.) Has $1/2''$ knockouts and screw holes 12" on center in back. Made of 20 gauge galvanized iron, unfinished.	72 ft	70 lbs.
8801	Channel Coupling: For connecting sections of channel together when installation is over 12' long.	5	1/ ₂ lb.
8802	Service Box: For feed end of system. Furnished with four $\frac{1}{2}$ knockouts and removable top plate.	5	2 lbs.
8803	End Cap: Used for closing end of channel. Provided with $\frac{1}{2}$ knockout for electrical connection in event service box is not used.	5	1 lb.
8804	Blank Capping: Furnished in 18" lengths and finished in baked aluminum enamel. For filling in on channel where lamps are not used.	3	3 lbs.
8805	Ballast Clamp: Slips into lower lip in back of channel and holds ballast in place. Two required for each ballast.	10	1/ ₂ lb.

ONE-LIGHT SNAP-ON CHANNEL COVERS

Catalog	1	DESCRIPTION	Standard Package Quantity Weigh				
No.	Length	DESCRIPTION					
	Baked Aluminum Enamel Finish						
8810A 8810B 8810C 8810D	18" 24" 36" 48"	Channel Cover for one 18"-15w Lamp Channel Cover for one 24"-20w Lamp Channel Cover for one 36"-30w Lamp Channel Cover for one 48"-40w Lamp	12 12 6 6	10 lbs. 13 lbs. 10 lbs. 13 lbs.			
	Porcelain Enamel Finish						
8820A 8820B 8820C 8820D	18" 24" 36" 48"	Channel Cover for one 18"-15w Lamp Channel Cover for one 24"-20w Lamp Channel Cover for one 36"-30w Lamp Channel Cover for one 48"-40w Lamp	12 12 6 6	8 lbs. 10 lbs. 8 lbs. 10 lbs.			
	Polished Chromium Finish						
8830A 8830B 8830C 8830D	18" 24" 36" 48"	Channel Cover for one 18"-15w Lamp Channel Cover for one 24"-20w Lamp Channel Cover for one 36"-30w Lamp Channel Cover for one 48"-40w Lamp	12 12 6 6	10 lbs. 13 lbs. 10 lbs. 13 lbs.			

The listings above are for **unwired** and **unassembled** parts only and **do not include sockets, lamp starters, or ballasts.** Completely wired and assembled Light Strip is listed on page 35.

Note — No. 8800X Channel can be furnished in 18", 24", 36", 48", 72" and 96" lengths. See page 34.

ONE-LIGHT REFLECTORS

For Use With No. 8800X Channel and No. 8810 Series Snap-On Channel Covers

For 18", 24", 36" and 48" Fluorescent Lamps

These Reflectors can also be used with No. 4810 Series Channel Covers and No. 4800 Tulamp Channel

These reflectors are made for easy attachment to No. 8810 Series Snap-On Channel Covers, and are punched to clear sockets and lamp starters so that they can be applied after the Channel and Covers have been wired and assembled. Coupling clips are furnished at ends so that reflectors can be fastened together for greater rigidity on continuous installations. Cast Aluminum Ornamental End Plates for use with these reflectors are listed below.

ASYMMETRIC REFLECTORS

No. 8850 Series — ALZAK (SPECULAR)

Catalog	Length	Description	Standard Package	
No.	Lengin	Description	Quantity	Weight
8850A	18"	Reflector only for one 18" Lamp	6	4 lbs.
8850B	24"	Reflector only for one 24" Lamp	6	5 lbs.
8850 C	36"	Reflector only for one 36" Lamp	4	5 lbs.
8850 D	48"	Reflector only for one 48" Lamp	3	5 lbs.

No. 8860 Series - PORCELAIN ENAMEL (DIFFUSE)

Catalog	Length	Description	Standar	d Package
No.	Lengin	bescription.	Quantity	Weight
8860A	18"	Reflector only for one 18" Lamp	6	10 lbs.
8860B	24"	Reflector only for one 24" Lamp	6	12 lbs.
88 60C	36"	Reflector only for one 36" Lamp	4	12 lbs.
8860D	48"	Reflector only for one 48" Lamp	3	12 lbs.

SYMMETRIC REFLECTORS

No. 8855 Series - ALZAK (SPECULAR)

Catalog	og Landh Barrindian		Standard	Standard Package	
No.	Length	Description	Quantity	Weight	
8855A 8855B 8855C	18" 24" 36"	Reflector only for one 18" Lamp Reflector only for one 24" Lamp Reflector only for one 36" Lamp	6 6 4	4 lbs. 5 lbs. 5 lbs.	
8855 D	48"	Reflector only for one 48" Lamp	3	5 lbs.	

No. 8865 Series - PORCELAIN ENAMEL (DIFFUSE)

Catalog		Danasia kian	Standar	d Package
No.	Length	Description	Quantity	Weight
8865A 8865B 8865C 8865D	18" 24" 36" 48"	Reflector only for one 18" Lamp Reflector only for one 24" Lamp Reflector only for one 36" Lamp Reflector only for one 48" Lamp	6 6 4 3	10 lbs. 12 lbs. 12 lbs. 12 lbs.

CAST ALUMINUM ORNAMENTAL END PLATES

For Use With All Reflectors Listed Above



Cat.	Description	Standa	rd Pkg.
No.	(Type)	Quantity	Weight
8808 8809	Asymmetric Symmetric	3 pair 3 pair	2 lbs. 2 lbs.




Illustrating Complete Assembly of Light Strip with Asymmetric Reflectors and Cast Ornamental End Plates



ASYMMETRIC REFLECTORS

No. 8850 Series—ALZAK (SPECULAR)
No. 8860 Series—PORCELAIN ENAMEL



DISTRIBUTION CURVES

ALZAK O PORCELAIN





SYMMETRIC REFLECTORS


No. 8855 Series—ALZAK (SPECULAR)
No. 8865 Series—PORCELAIN ENAMEL



DISTRIBUTION CURVES


ALZAK

PORCELAIN





Schedule S Discounts



Illustrating Complete Installations
• FOR TULAMP BALLASTS •











Snap-On Channel Covers



No. 4810 Series—BAKED ALUMINUM FINISH
No. 4820 Series—PORCELAIN ENAMEL FINISH
No. 4830 Series—POLISHED CHROMIUM FINISH



No. 4870 Series—BAKED ALUMINUM FINISH
No. 4860 Series—PORCELAIN ENAMEL FINISH
No. 4880 Series—POLISHED CHROMIUM FINISH



ST. LOUIS, MISSOURI

FLUORESCENT LIGHT STRIP

No. 4800 Series FOR TULAMP BALLASTS

For 18", 24", 36" and 48" Fluorescent Lamps

UNWIRED

A complete installation consists of (1) Channel, (2) Snap-on Channel Covers (size and number depends upon lamps used), (3) Ballast Clamps, (4) End Caps and (5) Coupling if installation is over 12' long. Asymmetric and Symmetric reflectors in porcelain enamel or specular Alzak can be applied if required. These reflectors are listed on page 31 for one lamp and page 33 for two lamps.

CHANNEL AND FITTINGS

Catalog	Description	STANDARD	PACKAGE
No.	Description		Weight
4800	Channel Only: (12' lengths.) Has 1/2" knockouts and screw holes approx. 195/8" on center in back. Made of 20 gauge galvanized iron, unfinished.	72 ft.	110 lbs.
4801	Channel Coupling: For connecting sections of channel together when installation is over 12' long.	5	3/4 lb.
4803	End Cap: For use with one-lamp channel covers. Used for closing end of channel. Provided with a 1/2" knockout for electrical connections.	6	$1\frac{1}{2}$ lbs.
4804	Blank Capping: For use with one-lamp channel covers. Furnished in 18" lengths and finished in baked aluminum enamel. Can be cut for filling in on channel where lamps are not used.	3	3½ lbs.
4805	Ballast Clamp: Slips into lower lip in back of channel and holds ballast in place. Two required for each ballast.	10	3/4 lb.
4806	End Cap: For use with two-lamp channel covers. Used for closing end of channel. Provided with $\frac{1}{2}$ knockout for electrical connections.	6	1½ lbs.
4807	Blank Capping: For use with two-lamp channel covers. Furnished in 18" lengths and finished in baked aluminum enamel. Can be cut for filling in on channel where lamps are not used.	3	4 lbs.

ONE-LAMP SNAP-ON CHANNEL COVERS

Catalog			STANDARD	PACKAGE				
No.	Length Description	Quantity	Weight					
	Baked Aluminum Enamel Finish							
4810A 4810B 4810C 4810D	18" 24" 36" 48"	Channel Cover for one 18"-15w Lamp Channel Cover for one 24"-20w Lamp Channel Cover for one 36"-30w Lamp Channel Cover for one 48"-40w Lamp	12 12 6 6	15 lbs. 20 lbs. 15 lbs. 20 lbs.				
		Porcelain Enamel Finish						
4820A 4820B 4820C 4820D	13" 24" 36" 48"	Channel Cover for one 18"-15w Lamp Channel Cover for one 24"-20w Lamp Channel Cover for one 36"-30w Lamp Channel Cover for one 48"-40w Lamp	12 12 6 6	12 lbs. 15 lbs. 12 lbs. 15 lbs.				
	Polished Chromium Finish							
4830A 4830B 4830C 4830D	18" 24" 36" 48"	Channel Cover for one 18"-15w Lamp Channel Cover for one 24"-20w Lamp Channel Cover for one 36"-30w Lamp Channel Cover for one 48"-40w Lamp	12 12 6 6	13 lbs. 17 lbs. 13 lbs. 17 lbs.				

TWO-LAMP SNAP-ON CHANNEL COVERS

Catalag			STANDARD	TANDARD PACKAGE Quantity Weight				
No	Length	Description	Quantity	Weight				
	Baked Aluminum Enamel Finish							
4870A 4870B 4870C 4870D	18" 24" 36" 48"	Channel Cover for two 18"-15w Lamps Channel Cover for two 24"-20w Lamps Channel Cover for two 36"-30w Lamps Channel Cover for two 48"-40w Lamps	12 12 6 6	17 lbs. 22 lbs. 17 lbs. 22 lbs.				
		Porcelain Enamel Finish						
4860A 4860B 4860C 4860D	18" 24" 36" 48"	Channel Cover for two 18"-15w Lamps Channel Cover for two 24"-20w Lamps Channel Cover for two 36"-30w Lamps Channel Cover for two 48"-40w Lamps	12 12 6 6	13 lbs. 16 lbs. 13 lbs. 16 lbs.				
	Polished Chromium Finish							
4880A 4880B 4880C 4880D	18" 24" 36" 48"	Channel Cover for two 18"–15w Lamps Channel Cover for two 24"–20w Lamps Channel Cover for two 36"–30w Lamps Channel Cover for two 48"–40w Lamps	12 12 6 6	14 lbs. 18 lbs. 14 lbs. 18 lbs.				

The listings above are for **unwired** and **unassembled** parts only and **do not include sockets, lamp starters, or ballasts.** Completely wired and assembled Light Strip is listed on page 36.

Note — No 4800 Channel can be furnished in 36", 48", 72" and 96" lengths. See page 34.

TWO-LIGHT REFLECTORS

FOR TWO LAMPS PARALLEL

For Use With No. 4800 Channel and No. 4870 Series **Snap-On Channel Covers**

For 18", 24", 36" and 48" Fluorescent Lamps

These reflectors are made for easy attachment to No. 4870 Series Snap-On Channel Covers, and are punched to clear sockets and lamp starters so that they can be applied after the Channel and Covers have been wired and assembled. Coupling clips are furnished at ends so that reflectors can be fastened together for greater rigidity on continuous installations. Cast Aluminum Ornamental End Plates for use with these reflectors are listed below.

ASYMMETRIC REFLECTORS

No. 4890 Series — ALZAK (SPECULAR)

Catalog	1 4			d Package
No.	Length	Description	Quantity	Weight
4890A	18"	Reflector only for two 18" Lamps	6	5 lbs.
4890B	24"	Reflector only for two 24" Lamps	6	7 lbs.
4890C	36"	Reflector only for two 36" Lamps	4	7 lbs.
4890D	48"	Reflector only for two 48" Lamps	3	7 lbs.

No. 4875 Series - PORCELAIN ENAMEL (DIFFUSE)

Catalog	1 4	D	Standard Package	
No.	Length	Description	Quantity	Weight
4875A 4875B 4875C 4875D	18" 24" 36" 48"	Reflector only for two 18" Lamps Reflector only for two 24" Lamps Reflector only for two 36" Lamps Reflector only for two 48" Lamps	6 6 4	15 lbs. 20 lbs. 20 lbs. 20 lbs.

SYMMETRIC REFLECTORS

No. 4895 Series - ALZAK (SPECULAR)

Catalog Le	l an ath	Donnin Ainm	Standard Package	
	Length	Description	Quantity	Weight
4895A	18"	Reflector only for two 18" Lamps	6 6	5 lbs.
4895B	24"	Reflector only for two 24" Lamps		7 lbs.
4895 C	36"	Reflector only for two 36" Lamps	3	7 lbs.
4895 D	48"	Reflector only for two 48" Lamps		7 lbs.

No. 4885 Series - PORCELAIN ENAMEL (DIFFUSE)

Catalog	Lamath	Describitor	Standard Package	
No.	Lengin	Length Description	Quantity	Weight
4885A	18"	Reflector only for two 18" Lamps	6	15 lbs.
4885B	24"	Reflector only for two 24" Lamps	6	20 lbs.
4885 C	36"	Reflector only for two 36" Lamps	4	20 lbs.
4885 D	48"	Reflector only for two 48" Lamps	3	20 lbs.

CAST ALUMINUM ORNAMENTAL END PLATES

For Use With All Reflectors Listed Above




Cat.	Description	Standa	ndard Pkg.	
No.	(Type)			
4808 4809	Asymmetric Symmetric	3 pair 3 pair	3 lbs. 3 lbs.	

Illustrating Complete Assembly of Light Strip with Asymmetric Reflectors and Cast Ornamental End Plates



ASYMMETRIC REFLECTORS

No. 4890 Series — ALZAK (SPECULAR) No. 4875 Series - PORCELAIN ENAMEL



CURVES

ALZAK

PORCELAIN





SYMMETRIC REFLECTORS

No. 4895 Series — ALZAK (SPECULAR) No. 4885 Series - PORCELAIN ENAMEL




DISTRIBUTION CURVES ALZAK

PORCELAIN







SHORT CHANNEL SECTIONS FOR SINGLE UNIT APPLICATIONS




















LIGHT STRIP ACCESSORIES

Short Channel Sections

Short sections of **Nos. 8800X** and **4800** Channel, to be used in conjunction with one and two-light Channel Covers, Fittings and Reflectors listed on pages 30, 31, 32, and 33.

These are available in various lengths as listed in the schedule below. They are finished in **baked aluminum enamel** and have knockouts in back for various mounting arrangements and electrical connections.


SHORT LENGTHS OF No. 8800X CHANNEL

Catalog No.		Will Accommodate Channel Covers and Reflectors for Number of Lamps	STANDARD PACKAGE	
	Length		Quantity	Weight
8800A	18"	1—18″	1 12	18 lbs.
8800B	24"	1—24″	12	23 lbs.
8800C	36"	1—36″	6	18 lbs.
8800D	48"	1—48″	6	23 lbs.
8800E	72″	2—36″	6	36 lbs.
8800F	96″	2—48″	6	46 lbs.

SHORT LENGTHS OF No. 4800 CHANNEL

Catalog No.	Length	Will Accommodate Channel Covers and Reflectors for Number of Lamps	STANDARD PACKAGE	
			Quantity	Weight
4800C	36″	l or 2—36"	1 6	26 lbs.
4800D	48"	1 or 2—48"	6	34 lbs.
4800E	72"	2 or 4—36"	6	52 lbs.
4800F	96″	2 or 4—48"	6	68 lbs.

Mounting Clamps, Brackets and Adjustable Fittings



Nos. 883 and 884 Mounting Brackets No. 885 Adjustable Ratchet Fitting Nos. 886 and 887 Ceiling Clamps

No. 882 Bench Clamp No. 888 Ceiling Flange

Bench Clamp — (No. 882) Can be used with $\frac{3}{8}$ " pipe and provides both vertical and swivel adjustment and portability.

Mounting Brackets — No. 883 for use with No. 8800X Channel and No. 8900 Series Wired Units, and No. 884 for use with No. 4800 Channel and No. 4900 Series Wired Units. They are easily attached to Channel or units after they have been assembled and wired. For use with $\frac{3}{8}$ " iron pipe.

Adjustable Ratchet Fitting — (No. 885) Used in conjunction with Mounting Brackets Nos. 883 and 884 will provide adjustment of lighting equipment to any angle.

Ceiling Clamps — (Nos. 886 and **887)** For installing assembled and wired Light Strip direct to ceiling. Also used in connection with Transom Bar Bracket. **Cast Ceiling Flange — (No. 888)** Accommodates $\frac{3}{8}$ " iron pipe.

Transom Bar Bracket — (No. 889) Used in connection with ceiling clamps for mounting units to transom bar. See illustration at left.

Catalog	5	STANDARD PACKAGE		
No.	Description	Quantity	Weight	
882	Bench Clamp	2	$\frac{4^{1}/_{2} \text{ lbs.}}{}$	
883	Mounting Bracket for 8800X Channel	10	$2^{1/2}$ lbs.	
884	Mounting Bracket for 4800 Channel	10	3 lbs.	
885	Adjustable Ratchet Fitting for 3/8" Pipe	4	2 lbs.	
886	Ceiling Clamp for 8800X Channel		2 lbs.	
887	Ceiling Clamp for 4800 Channel	10	2 lbs.	
888	Cast Ceiling Flange	4	2 lbs.	
889	Transom Bar Bracket	4	6 lbs.	

WIRED LIGHT STRIP

For One Row of Lamps

For 18", 24", 36" and 48" Fluorescent Lamps
(USING No. 8800X CHANNEL)

Wired With One-Lamp Ballasts

Complete assembled light strip for one row of lamps available in continuous lengths. This equipment is **wired with sockets**, **ballasts**, **lamp starters** and end fittings ready for installation. Long continuous sections will be furnished with all necessary fittings and parts for complete installation. The channel has screw holes and 1/2" knockouts in back on 12" centers for mounting and electrical connections. A 1/2" knockout is located in each end cap. Service box can be furnished in place of end cap, if desired. See illustration.

Porcelain enameled and specular Alzak reflectors, both asymmetric and symmetric shape, are listed on page 31. These reflectors can be applied to wired light strip after it is installed. If reflectors are to be employed, the light strip with baked aluminum enamel channel covers should be used.

One-Light Wired Light Strip

With BAKED ALUMINUM ENAMEL Channel Covers

	BASIC LAMP LENGTH			Apprax.
Catalag Na.	FOR LAMPS			Weight Each
	Na.	Size	Length	Lamp Length
W8810A	1	18″-15w-110v	191/4"	5 lbs.
W8810B	1	24″-20w-110v	251/4"	6 lbs.
W8810CA	1	36″-30w-220v	371/4"	8 lbs.
W8810CB	1	36″-30w-110v	371/4"	9 lbs.
W8810DA	1	48″-40w-220v	491/4"	10 lbs.
W8810DB	1	48″–40w–110v	491/4"	11 lbs.

One-Light Wired Light Strip


With PORCELAIN ENAMEL Channel Covers

	BASIC LAMP LENGTH			Apprax.
Catalag Na.		FOR LAMPS		Weight Each
110.	Na.	Size	Length	Lamp Length
W8820A	1	18″-15w-110v	191/4"	5 lbs.
W8820B	1	24"-20w-110v	251/4"	6 lbs.
W8820CA	1	36"-30w-220v	371/4"	8 lbs.
W8820CB	1	36″-30w-110v	371/4"	9 lbs.
W8820DA	1	48″-40w-220v	491/4"	10 lbs.
W8820DB	1	48″-40w-110v	491/4"	11 lbs.

One-Light Wired Light Strip

With POLISHED CHROMIUM Channel Covers

	BASIC LAMP LENGTH			Apprax.
Catalog Na.	FOR LAMPS		l	Weight Each
110.	Na.	Size	Length	Lamp Length
W8830A	1	18″-15w-110v	191/4"	5 lbs.
W8830B	1	24″-20w-110v	251/4"	6 lbs.
W8830CA	1	36″-30w-220v	371/4"	8 lbs.
W8830CB	1	36″-30w-110v	371/4"	9 lbs.
W8830DA	1	48″–40w–220v	491/4"	10 lbs.
W8830DB	1	48″-40w-110v	491/4"	ll lbs.



ILLUSTRATING WIRED LIGHT STRIP FOR ONE ROW OF LAMPS


No. W8810 Series
With Baked Aluminum Channel Covers
No. W8820 Series
With Porcelain Enamel Channel Covers
No. W8830 Series
With Polished Chromium Channel Covers



Huntington Woods Market, Royal Oak, Mich.

This Equipment Has Many Varied Applications . . . For Lighting Coves, Niches, Wallcases . . . For Decorative General Lighting, etc.






ILLUSTRATING WIRED LIGHT STRIP FOR ONE ROW OF LAMPS

No. W4810 Series
With Baked Aluminum Channel Covers
No. W4820 Series
With Porcelain Enamel Channel Covers
No. W4830 Series
With Polished Chromium Channel Covers

WIRED WITH TULAMP BALLASTS



ILLUSTRATING WIRED LIGHT STRIP FOR TWO LAMPS PARALLEL

No. W4870 Series
With Baked Aluminum Channel Covers
No. W4860 Series
With Porcelain Enamel Channel Covers
No. W4880 Series
With Polished Chromium Channel Covers

WIRED WITH TULAMP BALLASTS



WIRED LIGHT STRIP

For One and Two Rows of Lamps

For 18", 24", 36" and 48" Fluorescent Lamps

WIRED WITH TULAMP BALLASTS (USING No. 4800 CHANNEL)

Complete assembled light strip for one row of lamps, and two lamps parallel, available in continuous lengths. Wired with sockets, Tulamp ballasts*, lamp starters and end fittings ready for installation. Continuous wired strip of any length can be furnished. Maximum single length for shipping purposes 12'. Sections can be coupled on installation. Couplings and all necessary parts for complete installation are included. This equipment is listed basically for 36" and 48" lamps with 18" and 24" lamp lengths available for fill-in. Wired strip for one row of lamps is set up on a basic length of two lamps long.

The channel has screw holes and 1/2'' knockouts in back for mounting and electrical connections. A 1/2'' knockout is located in each end.

Porcelain enameled and specular Alzak reflectors, both asymmetric and symmetric shape, are listed on page 31 for one-lamp light strip and page 33 for two-lamp light strip. These reflectors can be applied to wired light strip after it is installed. If reflectors are to be employed the light strip with baked aluminum enamel channel covers should be used.
*Single ballast used on odd lamp.

FOR ONE ROW OF LAMPS

		BASIC LAMP LENGTH		Approx.		
Catalog No.		FOR LAMPS	Length	Weight Each		
	No.	Size	Lengin	Lamp Length		
With	Baked	Aluminum Enamel	Channel Co	vers		
W4810CA	2	36″-30w-220v	721/4"	12 lbs.		
W4810CB	2 2	36″-30w-110v	721/4"	12 lbs.		
W4810DA W4810DB	2	48"-40w-220v 48"-40w-110v	96 ¹ / ₄ " 96 ¹ / ₄ "	15 lbs. 15 lbs.		
	With Po	rcelain Enamel Cha	nnel Covers			
W4820CA	2	36"-30w-220v	721/4"	12 lbs.		
W4820CB	2	36″-30w-110v	721/4"	12 lbs.		
W4820DA	2 2	48″-40w-220v	961/4"	15 lbs.		
W4820DB	2	48"-40w-110v	961/4"	15 lbs.		
W	With Pelished Chromium Channel Covers					
W4830CA	2	36″-30w-220v	721/4"	12 lbs.		
W4830CB	2 2	36″-30w-110v	721/4"	12 lbs.		
W4830DA	2	48″-40w-220v	961/4"	15 lbs.		
W4830DB	2	48″-40w-110v	961/4"	15 lbs.		

FOR TWO LAMPS PARALLEL

Catalog No.		BASIC LAMP LENGTH		Approx. Weight Each	
	No.	Size	Length	Lamp Length	
With	Baked	Aluminum Enamel	Channel Co	vers	
W4870CA W4870CB W4870DA W4870DB	2 2 2 2	36"-30w-220v 36"-30w-110v 48"-40w-220v 48"-40w-110v	36 ¹ / ₄ " 36 ¹ / ₄ " 48 ¹ / ₄ " 48 ¹ / ₄ "	16 lbs. 16 lbs. 19 lbs. 19 lbs.	
V	Vith Por	celain Enamel Char	nnel Covers		
W4860CA W4860CB W4860DA W4860DB	2 2 2 2	36"-30w-220v 36"-30w-110v 48"-40w-220v 48"-40w-110v	36 ¹ / ₄ " 36 ¹ / ₄ " 48 ¹ / ₄ " 48 ¹ / ₄ "	16 lbs. 16 lbs. 19 lbs. 19 lbs.	
W	With Polished Chromium Channel Covers				
W4880CA W4880CB W4880DA W4880DB	2 2 2 2	36"-30w-220v 36"-30w-110v 48"-40w-220v 48"-40w-110v	36 ¹ / ₄ " 36 ¹ / ₄ " 48 ¹ / ₄ " 48 ¹ / ₄ "	16 lbs. 16 lbs. 19 lbs. 19 lbs.	

WIRED UNITS

FOR ONE OR TWO LAMPS

For 18", 24", 36" and 48" Fluorescent Lamps

Complete units furnished wired with lamp starters, ballasts, sockets and 3-foot wire lead. Levolier pull switch or toggle switch and cord and plug can be furnished if desired.

These units consist of Channel, End Caps and Channel Covers in various finishes as listed below.

Two-light units are furnished with Tulamp high power-factor ballasts.

Finish — Channel and end fittings are finished in baked aluminum enamel.


Standard Package — One fixture.

ONE-LAMP WIRED UNITS

Catalog		FOR LAMPS	Fixture	Weight	
No.	No.	Size	Length	Weighi	
With	h Baked	Aluminum Enamel	Channel Co	vers	
8910 8911 8912A 8912B 8913A 8913B	1 1 1 1 1 1 1	18"—15w—110v 24"—20w—110v 36"—30w—220v 36"—30w—110v 48"—40w—220v 48"—40w—110v	19 ¹ / ₄ " 25 ¹ / ₄ " 37 ¹ / ₄ " 37 ¹ / ₄ " 49 ¹ / ₄ " 49 ¹ / ₄ "	5 lbs. 6 lbs. 8 lbs. 9 lbs. 10 lbs. 11 lbs.	
	With P	orcelain Enamel Cha	nnel Covers		
8920 8921 8922A 8922B 8923A 8923B	1 1 1 1 1	18"—15w—110v 24"—20w—110v 36"—30w—220v 36"—30w—110v 48"—40w—220v 48"—40w—110v	19 ¹ / ₄ " 25 ¹ / ₄ " 37 ¹ / ₄ " 37 ¹ / ₄ " 49 ¹ / ₄ "	5 lbs. 6 lbs. 8 lbs. 9 lbs. 10 lbs. 11 lbs.	
AP-DITION OF	With Polished Chromium Channel Covers				
8930 8931 8932A 8932B 8933A 8933B	1 1 1 1	18"—15w—110v 24"—20w—110v 36"—30w—220v 36"—30w—110v 48"—40w—220v 48"—40w—110v	19 ¹ / ₄ " 25 ¹ / ₄ " 37 ¹ / ₄ " 37 ¹ / ₄ " 49 ¹ / ₄ "	5 lbs. 6 lbs. 8 lbs. 9 lbs. 10 lbs. 11 lbs.	


TWO-LAMP WIRED UNITS

Catalog		FOR LAMPS	Fixture	Weight	
No.	No.	Size	Length	Weigin	
Wit	h Baked	Aluminum Enamel	Channel Co	vers	
4970 4971 4972A 4972B 4973A 4973B	2 2 2 2 2 2 2	18"—15w—110v 24"—20w—110v 36"—30w—220v 36"—30w—110v 48"—40w—220v 48"—40w—110v	18 ¹ / ₄ " 24 ¹ / ₄ " 36 ¹ / ₄ " 36 ¹ / ₄ " 48 ¹ / ₄ "	10 lbs. 12 lbs. 16 lbs. 16 lbs. 20 lbs. 20 lbs.	
	With Porcelain Enamel Channel Covers				
4960 4961 4962A 4962B 4963A 4963B	2 2 2 2 2 2	18"—15w—110v 24"—20w—110v 36"—30w—220v 36"—30w—110v 48"—40w—220v 48"—40w—110v	18 ¹ / ₄ " 24 ¹ / ₄ " 36 ¹ / ₄ " 48 ¹ / ₄ " 48 ¹ / ₄ "	10 lbs. 12 lbs. 16 lbs. 16 lbs. 20 lbs. 20 lbs.	
	With Polished Chromium Channel Covers				
4980 4981 4982A 4982B 4983A 4983B	2 2 2 2 2 2	18"—15w—110v 24"—20w—110v 36"—30w—220v 36"—30w—110v 48"—40w—220v 48"—40w—110v	18 ¹ / ₄ " 24 ¹ / ₄ " 36 ¹ / ₄ " 36 ¹ / ₄ " 48 ¹ / ₄ "	10 lbs. 12 lbs. 16 lbs. 16 lbs. 20 lbs. 20 lbs.	




ONE-LAMP WIRED UNITS

No. 8910 Series
With Baked Aluminum Channel Covers
No. 8920 Series
With Porcelain Enamel Channel Covers
No. 8930 Series
With Polished Chromium Channel Covers




TWO-LAMP WIRED UNITS

No. 4970 Series
With Baked Aluminum Channel Covers
No. 4960 Series
With Porcelain Enamel Channel Covers
No. 4980 Series
With Polished Chromium Channel Covers







ASYMMETRIC TYPE

No. 8950 Series — ALZAK (Specular) Reflectors No. 8960 Series — PORCELAIN ENAMEL Reflectors




DISTRIBUTION CURVES

ALZAK








SYMMETRIC TYPE

No. 8955 Series — ALZAK (Specular) Reflectors No. 8965 Series — PORCELAIN ENAMEL Reflectors



DISTRIBUTION CURVES

ALZAK

PORCELAIN





ONE-LIGHT WIRED UNITS

For 18", 24", 36" and 48" Fluorescent Lamps

With Asymmetric and Symmetric Specular Alzak or Porcelain Enamel Reflectors

Complete units furnished wired with lamp starters, ballasts, sockets and 3-foot wire lead. Levolier pull switch or toggle switch and cord and plug can be furnished if desired. Units are complete with end caps, channel covers, Cast Ornamental End Plates and either specular Alzak or porcelain enamel reflectors as listed below.

Finish — Channel, end caps, channel covers and Cast Ornamental End Plates, baked aluminum enamel.

Standard Package — One fixture.

With ALZAK (Specular) ASYMMETRIC Reflectors

Cotolog No.		FOR LAMPS	Fixture	Weight
	No.	Size	Length	Eoch
8950	<u> </u>	18″—15w—110v	191/4"	6 lbs.
8951	1	24″—20w—110v	251/4"	7 lbs.
8952A	1	36″—30w—220v	371/4"	10 lbs.
8952B	1	36″—30w—110v	371/4"	ll lbs.
8953A	1	48″—40w—220v	491/4"	12 lbs.
8953B	l 1	48″—40w—110v	491/4"	13 lbs.

With PORCELAIN Enamel ASYMMETRIC Reflectors

Cotalog No.		FOR LAMPS Fixture		Weight
	No.	Size	Length	Each
8960	l	18″—15w—110v	191/4"	7 lbs.
8961	1	24"—20w—110v	251/4"	9 lbs.
8962A	1	36″—30w—220v	371/4"	12 lbs.
8962B	1	36″—30w—110v	371/4"	13 lbs.
8963A	1	48"—40w—220v	491/4"	14 lbs.
8963B	1	48″—40w—110v	491/4"	15 lbs.

With ALZAK (Specular) SYMMETRIC Reflectors

Cotalog No.		FOR LAMPS	Fixture	Weight
	No.	Size	Length	Eoch
8955	1	18″—15w—110v	191/4"	6 lbs.
8956	1	24″—20w—110v	251/4"	7 lbs.
8957A	1	36″—30w—220v	371/4"	10 lbs.
8957B	1	36″—30w—110v	371/4"	ll lbs.
8958A	1	48″—40w—220v	491/4"	12 lbs.
8958B	1	48″—40w—110v	491/4"	13 lbs.

With PORCELAIN Enamel SYMMETRIC Reflectors

Cotalog No. No		FOR LAMPS Fixture		Weight
	No.	Size	Length	Eoch
8965	1	18″—15w—110v	191/4"	7 lbs.
8966	1	24"—20w—110v	251/4"	9 lbs.
8967A	1	36″—30w—220v	371/4"	12 lbs.
8967B	1	36″—30w—110v	371/4"	13 lbs.
8968A	1	48″—40w—220v	491/4"	14 lbs.
8968B	l	48″—40w—110v	491/4"	15 lbs.

Note — These fixtures can be furnished without Cast Ornamental End Plates if desired.



TWO-LIGHT WIRED UNITS

• TWO-LAMPS LONG •

For 36" and 48" Fluorescent Lamps

With Asymmetric and Symmetric

Specular Alzak or Porcelain Enamel Reflectors

Complete units furnished wired with lamp starters, ballasts, sockets and 3-foot wire lead. Levolier pull switch or toggle switch and cord and plug can be furnished if desired. Units are complete with end caps, channel covers, Cast Ornamental End Plates and either specular Alzak or porcelain enamel reflectors as listed below.

Finish — Channel, end caps, channel covers and Cast Ornamental End Plates, baked aluminum enamel.

Standard Package — One fixture.

With ALZAK (Specular) ASYMMETRIC Reflectors

Catalog		FOR LAMPS	Fixture	Weight
No.	No.	Size	Length	Each
8952AX 8952BX 8953AX 8953BX	2 2 2	36"—30w—220v 36"—30w—110v 48"—40w—220v 48"—40w—110v	73 ¹ / ₄ " 73 ¹ / ₄ " 97 ¹ / ₄ " 97 ¹ / ₄ "	17 lbs. 19 lbs. 21 lbs. 23 lbs.

With PORCELAIN Enamel ASYMMETRIC Reflectors

Catalog No.		FOR LAMPS	Fixture	Weight
	Na.	Size	Length	Each
8962AX	2	36"—30w—220v	731/4"	21 lbs.
8962BX	2	36″—30w—110v	731/4"	23 lbs.
8963AX	2	48″—40w—220v	971/4"	25 lbs.
8963BX	2	48″—40w—110v	971/4"	27 lbs.


With ALZAK (Specular) SYMMETRIC Reflectors


Catolog		FOR LAMPS	Fixture Weight	
No.	No.	Size	Length	Each
8957AX 8957BX 8958AX 8958BX	2 2 2 2	36"—30w—220v 36"—30w—110v 48"—40w—220v 48"—40w—110v	73 ¹ / ₄ " 73 ¹ / ₄ " 97 ¹ / ₄ " 97 ¹ / ₄ "	17 lbs. 19 lbs. 21 lbs. 23 lbs.

With PORCELAIN Enamel SYMMETRIC Reflectors

Catalag		FOR LAMPS	Fixture Weight	
No.	Na.	Size	Length	Each
8967AX 8967BX 8968AX 8968BX	2 2 2 2	36"—30w—220v 36"—30w—110v 48"—40w—220v 48"—40w—110v	73 ¹ / ₄ " 73 ¹ / ₄ " 97 ¹ / ₄ " 97 ¹ / ₄ "	21 lbs. 23 lbs. 25 lbs. 27 lbs.

Note — These fixtures can be furnished without Cast Ornamental End Plates if desired.





ASYMMETRIC TYPE

No. 8952AX Series — ALZAK (Specular) Reflectors
No. 8962AX Series — PORCELAIN ENAMEL Reflectors




DISTRIBUTION CURVES

ALZAK

PORCELAIN





SYMMETRIC TYPE

No. 8957AX Series — ALZAK (Specular) Reflectors No. 8967AX Series — PORCELAIN ENAMEL Reflectors



DISTRIBUTION CURVES


ALZAK

PORCELAIN






Schedule S Discounts



ASYMMETRIC TYPE

No. 4990 Series — ALZAK (Specular) Reflectors
No. 4975 Series — PORCELAIN ENAMEL Reflectors




DISTRIBUTION CURVES

ALZAK


PORCELAIN





SYMMETRIC TYPE


No. 4995 Series — ALZAK (Specular) Reflectors
No. 4985 Series — PORCELAIN ENAMEL Reflectors



DISTRIBUTION
CURVES

ALZAK

PORCELAIN



Day Brite
Lighting, Inc.
St. LOUIS, MISSOURI

TWO-LIGHT WIRED UNITS

• TWO-LAMPS PARALLEL •

For 18", 24", 36" and 48" Fluorescent Lamps

With Asymmetric and Symmetric Specular Alzak or Porcelain Enamel Reflectors

Complete units furnished wired with lamp starters, Tulamp ballasts, sockets and 3-foot wire lead. Levolier pull switch or toggle switch and cord and plug can be furnished if desired. These units consist of channel, end caps, channel covers, Cast Ornamental End Plates and either specular Alzak or porcelain enamel reflectors as listed below.

Finish — Channel, end caps, channel covers and Cast Ornamental End Plates, baked aluminum enamel.

Standard Package — One fixture.

With ALZAK (Specular) ASYMMETRIC Reflectors

Catalog		FOR LAMPS	Fixture Weight	Weight
No.	No.	Size	Length	Each
4990	2	18″—15w—110v	181/4"	12 lbs.
4991	2	24″—20w—110v	241/4"	13 lbs.
4992 A	2	36″—30w—220v	361/4"	18 lbs.
4992B	2	36″—30w—110v	361/4"	18 lbs.
4993A	2	48″—40w—220v	481/4"	22 lbs.
4993B	2	48″—40w—110v	481/4"	22 lbs.

With PORCELAIN Enamel ASYMMETRIC Reflectors

Catalog		FOR LAMPS	Fixture	Weight
No.	No.	Size	Length	Each
4975	2	18″—15w—110v	181/4"	13 lbs.
4976	2	24″—20w—110v	241/4"	15 lbs.
4977A	2	36″—30w—220v	361/4"	21 lbs.
4977B	2	36″—30w—110v	361/4"	21 lbs.
4978A	2	48″—40w—220v	481/4"	27 lbs.
4978B	2	48″—40w—110v	481/4"	27 lbs.


With ALZAK (Specular) SYMMETRIC Reflectors

Cotalog		FOR LAMPS	Fixture	ture Weight
No.	No.	Size	Length	Eoch
4995	2	18″—15w—110v	181/4"	12 lbs.
4996	2	24″—20w—110v	241/4"	13 lbs.
4997 A	2	36″—30w—220v	361/4"	18 lbs.
4997B	2	36″—30w—110v	361/4"	18 lbs.
4998A	2	48″—40w—220v	481/4"	22 lbs.
4998B	2	48″—40w—110v	481/4"	22 lbs.

With PORCELAIN Enamel SYMMETRIC Reflectors

Cotalog No.		FOR LAMPS	Fixture Weight	Weight
	No.	Size	Length	Each
4985	2	18″—15w—110v	181/4"	13 lbs.
4986	2	24″—20w—110v	241/4"	15 lbs.
4987A	2	36″—30w—220v	361/4"	21 lbs.
4987B	2	36″—30w—110v	361/4"	21 lbs.
4988A	2	48"—40w—220v	481/4"	27 lbs.
4988B	2	48"—40w—110v	481/4"	27 lbs.

Note — These fixtures can be furnished without Cast Ornamental End Plates if desired.



FOUR-LIGHT WIRED UNITS

TWO-LAMPS PARALLEL

For 36" and 48" Fluorescent Lamps

0

With Asymmetric and Symmetric Specular Alzak or Porcelain Enamel Reflectors

Complete units furnished wired with lamp starters, Tulamp ballasts, starting compensators, sockets and 3-foot wire lead. Levolier pull switch or toggle switch and cord and plug can be furnished if desired. Units are complete with end caps, channel covers, Cast Ornamental End Plates and either specular Alzak or porcelain enamel reflectors as listed below.

Finish — Channel, end caps, channel covers and Cast Ornamental End Plates, baked aluminum enamel.

Standard Package — One fixture.

With ALZAK (Specular) ASYMMETRIC Reflectors

Catalog No.		FOR LAMPS	Fixture Weight	Weight
	No.	Size	Length	Each
4992AX	4	36″—30w—220v	721/4"	35 lbs.
4992BX	4	36″—30w—110v	721/4"	35 lbs.
4993AX	4	48″—40w—220v	961/4"	42 lbs.
4993BX	4	48″—40w—110v	961/4"	42 lbs.

With PORCELAIN Enamel ASYMMETRIC Reflectors

Catalog No.		FOR LAMPS	Fixture	Weight
	No.	Size	Length	Each
4977AX	4	36"—30w—220v	721/4"	42 lbs.
4977BX	4	36"—30w—110v	721/4"	42 lbs.
4978AX	4	48″—40w—220v	961/4"	52 lbs.
4978BX	4	48″—40w—110v	961/4"	52 lbs.

With ALZAK (Specular) SYMMETRIC Reflectors


Cotalog		FOR LAMPS	Fixture	Weight
No.	No.	Size	Length	Each
4997AX	4	36"—30w—220v	721/4"	35 lbs.
4997BX	4	36"—30w—110v	721/4"	35 lbs.
4998AX	4	48″—40w—220v	961/4"	42 lbs.
4998BX	4	48″—40w—110v	961/4"	42 lbs.

With PORCELAIN Enamel SYMMETRIC Reflectors

Cotolog		FOR LAMPS	Fixture Weight	Weight
No.	No.	Size	Length	Each
4987AX	4 4	36"—30w—220v	721/ ₄ "	42 lbs.
4987BX		36"—30w—110v	721/ ₄ "	42 lbs.
4988AX	4 4	48"—40w—220v	96 ¹ / ₄ "	52 lbs.
4988BX		48"—40w—110v	96 ¹ / ₄ "	52 lbs.


Note — These fixtures can be furnished without Cast Ornamental End Plates if desired.





ASYMMETRIC TYPE


No. 4992AX Series—ALZAK (Specular) Reflectors No. 4977AX Series—PORCELAIN ENAMEL Reflectors




DISTRIBUTION CURVES

ALZAK


PORCELAIN





SYMMETRIC TYPE

No. 4997AX Series—ALZAK (Specular) Reflectors
No. 4987AX Series—PORCELAIN ENAMEL Reflectors




DISTRIBUTION
CURVES

ALZAK

PORCELAIN








ONE-LAMP UNWIRED UNITS

No. U8910 Series
With Baked Aluminum Channel Covers
No. U8920 Series
With Porcelain Enamel Channel Covers
No. U8930 Series
With Polished Chromium Channel Covers



TWO-LAMP UNWIRED UNITS

No. U4970 Series


With Baked Aluminum Channel Covers

No. U4960 Series

With Porcelain Enamel Channel Covers

No. U4980 Series

With Polished Chromium Channel Covers





UNWIRED UNITS

Without Reflectors, Ballasts, Sockets or Lamp Starters

FOR ONE AND TWO LAMPS

For 18", 24", 36" and 48" Fluorescent Lamps

These knock-down units are listed for one and two lamps, 18", 24", 36" and 48" size. They include channel, end caps, ballast clamps and snap-on covers (cover finishes listed in schedule below). Channel and end fittings are finished in baked aluminum enamel.

Two-lamp units will accommodate Tulamp ballasts.

By adding reflectors and Cast Ornamental End Plates listed on pages 31 and 33, complete reflector units can be made.

ONE-LAMP UNWIRED UNITS

Catalog	F	OR LAMPS	Fixture	Standard Package		
No.	No.	Size	Length	Quantity	Weight	
Wi	With Baked Aluminum Enamel Channel Covers					
U8910 U8911 U8912 U8913		18"—15w 24"—20w 36"—30w 48"—40w	19 ¹ / ₄ " 25 ¹ / ₄ " 37 ¹ / ₄ " 49 ¹ / ₄ "	12 12 6 6	34 lbs. 40 lbs. 34 lbs. 40 lbs.	
	With F	orcelain Enan	nel Channel	Covers		
U8920 U8921 U8922 U8923	1 1 1	18"—15w 24"—20w 36"—30w 48"—40w	19 ¹ / ₄ " 25 ¹ / ₄ " 37 ¹ / ₄ " 49 ¹ / ₄ "	12 12 6 6	32 lbs. 37 lbs. 32 lbs. 37 lbs.	
	With Polished Chromium Channel Covers					
U8930 U8931 U8932 U8933		18"—15w 24"—20w 36"—30w 48"—40w	19 ¹ / ₄ " 25 ¹ / ₄ " 37 ¹ / ₄ " 49 ¹ / ₄ "	12 12 6 6	34 lbs. 40 lbs. 34 lbs. 40 lbs.	

TWO-LAMP UNWIRED UNITS


Catalog	F	OR LAMPS	Fixture	Standard Package		
No.	No. Size		Length	Quantity	Weight	
Wi	th Bake	d Aluminum l	Enamel Cha	nnel Cove	rs	
U4970 U4971 U4972 U4973	2 18"—15w 2 24"—20w 2 36"—30w 2 48"—40w		18 ¹ / ₄ " 24 ¹ / ₄ " 36 ¹ / ₄ " 48 ¹ / ₄ "	12 12 6 6	47 lbs. 60 lbs. 47 lbs. 60 lbs.	
	With I	Porcelain Enar	nel Channel	Covers		
U4960 U4961 U4962 U4963	2 2 2 2	18"—15w 24"—20w 36"—30w 48"—40w	18 ¹ / ₄ " 24 ¹ / ₄ " 36 ¹ / ₄ " 48 ¹ / ₄ "	12 12 6 6	43 lbs. 46 lbs. 43 lbs. 46 lbs.	
	With P	olished Chrom	ium Channe	l Covers		
U4980 U4981 U4982 U4983	2 2 2 2	18"—15w 24"—20w 36"—30w 48"—40w	18 ¹ / ₄ " 24 ¹ / ₄ " 36 ¹ / ₄ " 48 ¹ / ₄ "	12 12 6 6	45 lbs. 47 lbs. 45 lbs. 47 lbs.	


HOSPITAL LIGHTING FIXTURES

For 48" Fluorescent Lamps

HIGH INTENSITY
LIGHTING . . . FOR
OPERATING TABLES

Schedule O Discounts





Lighting equipment for operating rooms must meet many rigid requirements demanded for this particular type of work. It must be specifically designed so as to provide maximum intensities in the operating area and at the same time, be free from shadows and glare.


Another very important requirement for this type of lighting demands that while the highest intensities possible must be provided, the light must be **cool.** Fluorescent lamps provide the ideal solution to this problem in that they provide high intensities at minimum wattages for cool, shadowless, glare-free illumination. In fact, the radiant heat given off by Fluorescent lamps is only one-fifth of that given off by incandescent sources of equal wattages.

Day-Brite Operating Table Fixtures are designed to be adaptable to various applications. A complete system consists of one center fixture for four 48" lamps and four side fixtures for two 48" lamps each. These fixtures are installed on the ceiling, above the operating table in direct relation to their beam characteristics. Each individual installation must be laid out by us before fixtures are installed in order to insure satisfactory results. Send complete details of operating room, such as measurements of room, location of table, etc.


Fixtures are made of steel and are finished in white baked enamel. Reflectors are SPECULAR ALZAK ALUMINUM and are engineered to provide maximum controlled output of illumination. All units are **wired** with **Tulamp ballasts** which practically eliminates stroboscopic effect. Starting compensators are included. All necessary knockouts are provided for electrical connections.


Standard Package — One set for a complete installation. (One Center Fixture and Four Side Fixtures.)

Catalog	Туре		FOR LAMPS	Length	Weight
No.	~	No.	Size		
8760A	Center	4	48″—40w—220v	481/4"	110 lbs.
8760B	Center	4	48″—40w—110v	481/4"	110 lbs.
8770A	Side	2	48″—40w—220v	481/4"	65 lbs.
8770B	Side	2	48″—40w—110v	481/4"	65 lbs.



VELUALUME*





Typical Distribution Curve
of the
UELUALUME

*T. M. Reg. U. S. Pat. Off.; Design Pats. Applied For



The Day-Brite **VELVALUME** will provide more light of a softer quality for all difficult visual tasks such as accounting, bookkeeping, billing, clerical work, drafting, layout work and kindred occupations. Its smooth appearance will harmonize with the finest architectural treatments and add a decorative touch to any interior. It is available for three and four 48''—40 watt fluorescent lamps and is especially designed and recommended for **direct ceiling mounting only.**

Smooth in Design . . . Rich in Appearance

General body of fixture is satin and polished finish. The smoothly streamlined cast aluminum ornamental ends have cleverly concealed louvers that highlight the fins, thus enhancing the general luminous appearance of the fixture.

Specifically Engineered for Maximum Efficiency

The side panels are of a newly designed high transmission SATINOL finished FLUTEX glass having an ornamental pattern that blends with the smart lines and modern appearance of the fixture. The SATINOL process increases diffusion and affords soft, restful illumination, and at the same time assures minimum depreciation.

The interior of the fixture is finished in baked white enamel providing a diffuse reflecting surface of maximum efficiency.

Arranged for Easy Installation

The **VELVALUME** is designed for easy installation. The entire fixture body is hinged to the ceiling plate and is easily opened for access to the interior for servicing. Ceiling plate is provided with all necessary mounting holes and knockouts for electrical connections.

Fixtures are completely wired, ready to install. They include **Tulamp** ballasts, sockets, lamp starters and starting compensators.

Standard Package — One fixture.

Catalog		FOR LAMPS		Weight		
No.	No. Size		Length Width			Depth
5773A* 5773B* 5774A 5774B	3 4 4 4	48"—40w—220v 48"—40w—110v 48"—40w—220v 48"—40w—110v	54 ¹ / ₂ " 54 ¹ / ₂ " 54 ¹ / ₂ " 54 ¹ / ₂ "	14" 14" 14" 14"	9 ¹ / ₄ " 9 ¹ / ₄ " 9 ¹ / ₄ " 9 ¹ / ₄ "	75 lbs. 75 lbs. 85 lbs. 85 lbs.

*One Tulamp and one one-lamp ballast used in three-light fixtures provides 85% power-factor.



ALPHABETICAL INDEX

BANK CAGE LIGHTING		Po	age	:					
			_						
		•	9						
Ceiling Lumingires				25					
	l Glass Type								
				18 18					
-				19					
•									
DISPLAY LIGHTING									
•	tures								
	ktures								
_					_				
-	3								
	es								
	ontinuous								
	-Light								
	nits and Continuous								
		• •	•	• •	10				
DRAFTING TABLE						10			
	tures		•		• •	12			
HOSPITAL LI							40		
	le Units		•			• •	43		
	IAL LIGHTING								
-	RTY"								
LIBR	ARY TABLE LIGHTING								
Librar	ry Table Fixtures							. 13	3
	LIGHT STRIP								
	General Information								
	For One Row of Lamps (UNWIRED) One-Light Reflectors								
	For Tulamp Ballasts (UNWIRED)								. 32
	Two-Light Reflectors								
	Wired Light Strip — One-Light								
	Wired Light Strip — One and Two-Light								
	One and Two-Light Wired Units — No Reflec One-Light Wired Units — With Reflectors								
	Two-Light Wired Units — With Reflectors (Tw								
	Two-Light Wired Units — With Reflectors (Tw	vo L	an	nps	Para	llel)			. 40
	Four-Light Wired Units — With Reflectors (Tr Unwired Units — One and Two-Lamp								
, 1 7.	SHOW WINDOW LIGHTING	•		•		•			
7.7	Show Window Footlights								13
	Show Window Reflectors								



Numerical Index

	C + N C - d - D	Cost No.	CAN CA D
Cat. No. Code Page	Cat. No. Code Page	Cat. No. Code Page	Cat. No. Code Page
FY1 5	888dap34	1432dynam 6	2248B goiter17
FZ1 5	88934	1433dyname 6	2315 l7
FY2	914diaour 3	1440deis 5	2318golem17
FZ2 5	915gibber3	14415	2324golf17
FY3	940ll	1442deist 5	2336Agonad17
FZ3 5	941garb11 9658	1443 deity	2336Bgoner17
11yelb 3	966daric8	1445 hien 5	2348A gong17 2348B goober17
12B yolk	970garble11	1446	2371 demit10
14B3	971garcon11	1447 hink	2950 gorsy
17yak 3	972garden11	1448 hill	2951 gospel 8
19A ypres 3	973gare11	1449	2952 gossip 8
140 gad3	974 garget11	1620 glair28	2953 goth
141 3	975garish11	1621 glaive28	2954 gothic18
142 3	980garlic11	1640gland28	2955 gouge18
143 gaffer 3	981ll	1641glans28	2956 gouger18
144 gage3	982 garnet11	1642A glave28	2957 gourd18
145 3	983ll	1642B glaze28	2958A 18
240A dab27	984 ll	1643Aglean28	2958B 18
240AW dabber27	985 .11	1643B gleve28	2959A 18
240AX dabble27	990 ll	1645 glede28	2959B 18
240B dace27	991 .garth	1646 glee28	2960A grace 8
240BW 27	1040 9	1647Aglen28	2960B 8
240BX hime27	1041 9	1647B glib28	2961A gradin 8
240C dade27	1042 daswe9	1648A .glide28	2961B 8
240CW 27	1043 daub9	1648B glider28	2962A 8
240CX daff27	1044A daud 9	1650 gliff28	2962B 8
412 2	1044B daunt9	1651glim28	2963A 8
413	1045A dauw9	1652A glioma28	2963B 8
414A dago	1045B daw9	1652B gloat28	2964 grange18
414B	1046A dawk9	1653A globe28	2965granny18
415Adaint	1046B dawm9	1653B globin28	2966 grape18
415B	1047Adeas9	1655gloom28	2967grapho18
422	1047B gallon9	1656gloomy28	2968A 18
423 dawk	1085gauss9	1657A gloria28	2968B 18
424B daker2	1086gauze 9	1657B glory28	2969A 18
425A dal	1087Agavel 9	1658A glossa28 1658B glove28	2969B grater18 3230 gravy13
425B dale2	1087B gavial 9 1090 9	1660 glove28	3231 gravy13
642A gale12	1091gawk9	1661 glucic28	3232 grdze13
642B galea12	1092 gay 9	1662A gluey28	3233 .greed13
643A galena12	1093 garal9	1662B glum28	3570 denay22
643B galiot12	1094A gaze9	1663A glume28	3571A dene22
645 gall10	1094B 9	1663B glut28	3571B denier22
646A galley10	1095A gecko 9	1665 gluten28	3590 dense22
646B 10	1095B 9	1666 glyph28	3591A dent22
652A galoot12	1096A 9	1667A gnarl28	3591B 22
652B 12	1096B geezer 9	1667B gnash28	4800
653A galosh12	1097A .geld9	1668A gnat28	4800C .desse34
653B 12	1097B gelid9	1668B 28	4800D deter34
655 gambit10	1270 18	1770 gneiss12	4800E detent34
656A gamble10	1271 ghaut18	1771gnome12	4800F dette34
656B gambol10	1272ghazi18	1772Agnomic12	4801 deutr32
666dye21	1273ghetto18	1772Bgnosis12	4803deturb32
690gamely10	1278ghout18 1279giant18	1773Agnu12	4804 deuse32
691gamete10	1279 glant18 1280A decard13	1773B goa12 1780 goad12	4805 deuto32 4806 deva32
692A 10 692B 10	1280B decay13	1781goaf12	4807 deva32
710 gamin10	1281A decay13	1782Agoanna12	4808 devdst32
711gamut10	1281B. deci 13	1782Bgoat12	4809 devex33
712A gamp10	1282A decoct13	1783Agoatee12	4810A debil 32
712B gander10	1282B decoy13	1783Bgobble12	4810B devoir32
800 gang19	1283A .dedes13	2115 gyral17	4810C habit32
802 gangue19	1283B dedit13	2118 gob17	W4810CA hack36
806 gaol19	1290A deem13	2124 goblet17	W4810CB hackle36
808 .19	1290B 13	2136A goblin17	4810D 32
810 galak19	1291A 13	2136B goby17	W4810DA .hading36
866galaxy21	1291B deev13	2148A gocart17	W4810DB dewy36
866 galaxy22	1292A defly13	2148B 17	4820A dextrer32
882dandy34	1292B deflux13	2215 gyrate17	4820B 32
883demon34	1293A l3	2218 gidwit17	4820C deyeg ² 2
884damp34	1293B deign13	2224 17	W4820CA dial
885	1400gibbet 4	2236A goffer17	W4820CB dialy36
886	1430	2236B gog17	4820D diacid32
887 dant34	1431	2248A .goggle17	W4820DA .diana36



Numerical Index

Cat. No.	Code	Page	c
W4820DB.	diaper	36	4
4830A	hadj	32	4
4830B	hadji	32	4
4830C	hadst	32	4
W4830CA. W4830CB.	haema.	36	4
4830D	haa	32	U
W4830DA.	hail	36	Ιť
W4830DB.			4
4860A	hike	32	4
4860B	hale	32	U
4860C	\dots dibs \dots	32	4
W4860CA. W4860CB	hall	36	4
4860D	dicast	32	4
W4860DA.	haloid	36	1 4
W4860DB.	ham	36	4
4870A	dicing	32	4
4870B	dicker	32	4
4870C			4
W4870CA W4870CB			4 4
4870D	didal	32	4
W4870DA	diet	36	4
W4870DB.	dig	36	4
4875A			4
4875B			4
4875 C	doggba	33	4 4
4880A	dakiii	32	4
4880B	dakoon.	32	4
4880C	daiker	32	4
W4880CA	dainty	36	4
W4880CB.	dairi	36	4
4880D	daily	32	4
W4880DA W4880DB	dairy	36	4
4885A	dakoit	33	4
4885B	dacoit	33	4
4885C	dales	33	4
4885D	dalk	33	4
4890A 4890B			4
	hank		4
4890D	hanse	33	5
4895A	hanker.	33	5
4895B	hap	33	5
4895C	haply	33	5
4895 D 4960			5 5
U4960	dampy	42	5
4961	hare	37	5
U4961	damson.	42	5
4962A	hark	37	5
4962B	harem	37	5
U4962			5
4963A 4963B			5 5
U4963	dande	42	5
4970	harpy	37	C
U4970	dangle	42	S
	L	37	C
4971			S
U4971	danite		
U4971 4972A	danite	37	C
U4971 4972A 4972B	danite harry hash	37	S
U4971 4972A 4972B U4972	danite harry hash dapple	37	S
U4971	daniteharryhashdapplehaslethasp	37 37 37 37	S
U4971 4972A 4972B U4972 4973A 4973B	daniteharryhashdapplehaslethaspdargie	37 42 37 37 37	S
U4971	daniteharryhashdapplehaslethaspdargie	37 42 37 37 42	O S C S C S C
U4971	daniteharryhashdapplehaslethaspdargieha sthat	37 42 37 37 42 40	S
U4971	daniteharryhashdapplehaslethaspdargieha sthat	37 42 37 37 42 40 40	SC
U4971	daniteharryhashdapplehaslethaspdargiehathathathhathhath	37 42 37 37 42 40 40 40	SCSCSCS

_		
Cat. No. 4978A	Code	Page
4978A	.haw	40
4978AX	.hawk	41
4978B	hawok	40
4978BX	nawse	37
4980 U 4980	darkle	42
4981	darkly	37
4981 U4981	.darky	42
4982A	darnel	37
4982B U4982	.darner	42
4983A	.daroo	37
4983B	.dart	37
U4983	darter	42
4985	hay	40
4986 4987.A	hea	40
4987A 4987AX	heal	41
4987B 4987BX	.heap	40
4987BX	heady	41
4988A 4988AX	hear.	41
4988B	.heart	40
4988B 4988BX	.heat	41
4990	heath	40
4991	heave	40
4992A	heaves .	41
4992B 4992BX	.hecato .	40
4992BX	hector	41
4993A 4993AX	heed	40
4993B	heifer	40
4993B 4993BX	.heir	41
4995	helic	40
4996	hegira	40
4997A 4997AX	helic	40
4997 B .	.helix	40
4997BX	.helm	41
4998A 4998AX	.helo	40
4998 AX 4998 B	helve	40
4998BX	.hem	41
5224	.guff	25
5236A	.guffaw	25
5236B 5248 A	guffer	25
5248B	.guib	25
5324	.guidon	25
5336 A	.guile	25
5336B 5348 A	.guinea	25
5348B	.guitar	25
5424	.gula	25
5436A	.gular	25
5436B 5448A	gulch	25
5448 B	.gules	25
C5524	.does	23
S5524	·doff	23
C5525A	.dog	23
S5525A C5525B	.doggl	23
S5525B	.dogate	23
C5526A	.dogape.	23
S5526A	.doge	23
C5526B S5526B	.dogged	23
C5527A	.doit	23
S5527A	.doko	23
C5527B	.dolce	23
S5527B C5528 A	.dolent	23
S5528A	.doll	23

l Inde	×
Cat. No.	Code Page dolly23 23
C5528B	Holly23
5660	dorsa23
5660	dorsad24
5661	dorsad24
5662	dorse 23 dorse 24
5663	dorsel23
5663	dorsel24 dorsum23
5664	dorsum24
5670 5671	dorter23
5672	losage23
5673 C5724	dose23
\$5724	lose123
S5724	dosser23
S5725A	lot23
S5725B	lost23
C5726A	lotage23
C5726B	dotant23
\$5726B	lotard23
\$5727A	loting23
C5727B	lotty23
\$5727B	aste44
5773B l	at44
5774B l	ass44
\$5824X	nemp24
\$5824Z	nepat24
S5825AZh	nept
\$5825BZ	ner24
\$5826AX	ner
S5826BX	nern24
\$5826BZ	nero24
S5827AZ	nerse24
\$5827BX]	nest
S5828AX	new 24
S5828AZ	nexa24
\$5828BX \$5828BZ	nic24
C5918	adle23
S5918 l	aft23
\$5924	ag23
C5936B l	agan23
C5948B 1	ager23
\$5948B l	aic23
6248A	lough20
6248B	
6348A	loura20
6348B	louse20
6448A	love20
6448B6 6548A6	lowar20
6548B	lowel20
6648 B	lowf20
6748A	lowie20
6748B d	lowle20

Cat. No. 7218	Code	Page
7224	down	115
7236A	.dowry	15
236B	.dowse	15
248A	.dowve	15
248B	.dowy	15
318 324	dowser	15
336A	.doxy	15
336A 336B	.dozer	15
348A	.dozy	15
348B	.drab	15
418 424	.drachm	15
436A	drad	15
436B	draff	15
448A	.draffy	15
448B	.draft	15
448A	drag	20
248 B	.dragon	20
324	.drail	20
348A	.drain	20
348B	.draine	20
424	drake	20
448A 448B	drama	20
548A	.drank	20
548B	.drapet	20
648A 648B	.drasty	20
648B 748A	drat	20
748B	.draugh	20
760A	.drave	43
760B	.drawn	43
770A	dray	43
770B 800A	drazel	43
800 B	.drear	34
800 C	dredge	34
300 C	.dread	34
B00E	.dree	34
800F 800X	dreg	34
801	hide	30
B02	hiatus	30
803	hie	30
804	higgle	30
805 808	dreggy	31
XNY	drench	
810A	hilt	30
V8810A	dreng	35
810A V8810A 810B V8810B	hind	30
810 C	dress	30
810 C V8810 CA	dressy	35
V8810CB	drier	35
V8810CB	hinny	30
VXXIODA	drie	35
V8810 DB	dried	35
V8810DB 820A V8820A	drill	35
820 B	hispid	30
V8820B	drilly	35
8 20C	hiss	30
V8820CA	drink	35
V8820CB	drip	35
820D V8820DA	dripple	35
V8820DB	drive	35
V8820DB 830A	hither	30
V8830A	drogue	35
83UB	hive	30
V8830B	1 11	0.0



Numerical Index

Cat. No.	Code	Page	Cat. No.	Code	Page	Cat. No.	Code	Page	Cat. No.	Code	Page
8830C			U8912			8952B			8966		_
W8830CA.						8952BX					
W8830CB.			8913A			8953A			8967A 8967AX		
8830D			8913 B			8953AX			8967B		
W8830DA.			U8913			8953B			8967BX		
W8830DB.			8920 U8920			8953BX			8968A		
8850A			8921			8955			8968AX		
8850B			U8921			8956			8968B		
8850 C			8922A			8957A			8968BX		
8850 D			8922B			8957AX			9218		
8855A			U8922			8957B			9224		
8855 B			8923A			8957BX			9236A		
8855 C			8923 B			8958A			9236B		
8855 D			U8923			8958AX			9248A		
8860A			8930			8958 B			9248 B		
8860B			U8930			8958BX			9318		
8860C			8931			8960			9324		
8860D			U8931			8961			9336A		
8865A			8932A			8962A			9336B		
8865B			8932B			8962AX			9348A		
8865C			U8932	lano	42	8962B			9348B		
8865D			8933A			8962BX			9418		
8910			8933B			8963A			9424		
U8910			U8933			8963AX			9436A		
8911			8950			8963B			9436B		
U8911			8951			8963BX			9448A		
8912A			8952A			8965			9448B		
8912B			8952AX			0000	· · · · · · · · · · · · · · · · · · ·		3110 D	awen	15
UJILL	u1001	51	UJJLIAA	· · ur ytii. · ·							

Day-Brite Fixtures are Approved by the Underwriters' Laboratories


Union Wired and Union Fabricated

Our Engineering Department is At Your Service

In this catalog you will find listings of all standard Fluorescent lamp fixtures manufactured by Day-Brite. These fixtures have many and varied applications which will suggest themselves to you as your experience with the use of fluorescent lighting grows.

However, we realize that there will be many instances when you will have a particular lighting problem which will demand something special for its solution. In such cases, we offer you the experience of our competent staff of designers and engineers.

Let us know what your requirements are and we will do our best to provide the most practical solution. Do not hesitate to call upon us for this service... there is no obligation on your part.



LICHTING INC. YST.LOUIS MISSOURI

SALES OFFICES IN PRINCIPAL CITIES

UNITED STATES

CANADA · HAWAII · MEXICO · PHILIPPINES

GENERAL OFFICE AND FACTORY, 5411 BULWER AVE., ST. LOUIS, MO.

Y-40 50

1-41, 20M Reprint